

# Technical Datasheet



**Trade name :** Limescale Barracuda  
**Reviewed:** 10.12.2020  
**Date of print :** 10.12.2020

**Page :** 1 of 1

## Description

The powerful Limescale Barracuda acts strongly upon limescale, urine scale, rust, water stains, soap residues and metal tarnishing as well as light oils and fats. Limescale Barracuda is very easy in application and has a fresh smell. It is universally applicable for cleaning of acidic resistant surfaces in sanitary facilities, saunas and public swimming pools. Working powerful in the exterior on glass, stones, terracotta and stonewear.

## Chemical characterisation

Water-based acidic cleaning agent.

## Classification according to Regulation (EC) No.1272/2008 [CLP]

-

## Transport information

ADR : -

## Water hazard class (Classification according to AwSV)

Water hazard class : 1 (Slightly hazardous to water)

## Labelling for contents according to regulation (EC) No. 648/2004

< 5 % non-ionic surfactants  
perfume

## Safety equipment

Eye / Face protection:	suitable safety goggles acc. EN 166	In case of splash
Hand protection:	suitable gloves type EN 374	In case of possible or enduring skin contact
Respiratory protection:	Combination filtering device DIN EN 14387	In case of exceeding exposure limit values

## Application

Limescale Barracuda is ready to use, just spray it onto the surface, let it work for a short time and then rinse or wipe off with a damp cloth.

## Technical data

Appearance :	liquid		
Colour :	red		
Odour :	characteristic		
Boiling temperature :	ca. 100 °C	Solidifying temperature :	< 0 °C
Flash point :	not relevant	Ignition temperature :	not relevant
Lower explosion limit :	not relevant	Upper explosion limit :	not relevant
Density (20 °C) :	ca. 1 g/cm <sup>3</sup>	pH-value :	> 2
VOC (EG) :	0 Wt %	VOC (CH) :	0 Wt %

## Storage

Keep container tightly closed. Keep/store only in original container. Protect against sub-zero temperatures. Optimized storage temperature is between 2 °C up to 35 °C. The product is storable in closed original packaging for at least 12 months. Starting date is the date of production.

Storage class (acc. TRGS 510): 12

## Disposal advices

The waste codes are recommendations based on the schedule use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances.

**Waste code acc. EWC/AVV for unused product**  
20 01 29\* Detergents containing dangerous substances.

**Waste code acc. EWC/AVV for packaging**  
15 01 02 plastic packaging.

Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.

## Order information

<b>A50002</b>	500 ml PET bottle with trigger – TU: 20 x 500 ml ( 1 box)
<b>A01002</b>	10 l Jerry can
<b>A02002</b>	20 l Jerry can
<b>A20002</b>	200 l Drum
<b>A10002</b>	1000 l IBC