

**LOCTITE® LB 8040™**Known as Freeze & Release  
December 2016**PRODUCT DESCRIPTION**

LOCTITE® LB 8040™ provides the following product characteristics:

|                    |                |
|--------------------|----------------|
| <b>Technology</b>  | Lubricants     |
| Chemical Type      | Mineral Oil    |
| Color              | Amber          |
| <b>Cure</b>        | Not applicable |
| <b>Application</b> | Rust treatment |
| Dispense Method    | Spray          |
| Key Substrates     | Metals         |

LOCTITE® LB 8040™ is a special mineral oil formulation to free rusted, corroded and seized parts. The shock-freezing effect from a stream of lubricant at -43°C will instantly cool parts and cause microscopic cracks in the layer of rust. This allows the lubricating ingredients to wick directly into the rust by capillary action. Released parts remain lubricated and protected from corrosion.

**TYPICAL PROPERTIES**

|                                 |     |
|---------------------------------|-----|
| Density @ 20 °C, g/ml           | 0.6 |
| Maximum chill down, °C          | -43 |
| Lubricant viscosity, mPa·s (cP) | <5  |

**GENERAL INFORMATION**

**This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as a lubricant for chlorine or other strong oxidizing materials.**

**For safe handling information on this product, consult the Safety Data Sheet (SDS).**

**Handling Precautions**

Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on an open flame or any incandescent material. Keep away from sources of ignition.

**Directions For Use:**

1. Remove dirt and loose rust from parts
2. Shake can thoroughly. Spray at a distance of about 10 to 15 cm onto the fastener to be treated for 5 to 10 seconds
3. Allow the product to react for 1 to 2 minutes, before attempting to release the seized part
4. Repeat application if necessary

**Storage**

Store product in the unopened container in a dry location. Storage information may be indicated on the product container labeling.

**Optimal Storage: 8 °C to 21 °C. Storage below 8 °C or greater than 28 °C can adversely affect product properties.** Material removed from containers may be contaminated during use. Do not return product to the original container. Henkel Corporation cannot assume responsibility for product which has been contaminated or stored under conditions other than those previously indicated. If additional information is required, please contact your local Henkel Representative.

**Not for product specifications**

The technical data contained herein are intended as reference only. Please contact your local quality department for assistance and recommendations on specifications for this product.

**Conversions**

|                               |
|-------------------------------|
| (°C x 1.8) + 32 = °F          |
| kV/mm x 25.4 = V/mil          |
| mm / 25.4 = inches            |
| µm / 25.4 = mil               |
| N x 0.225 = lb                |
| N/mm x 5.71 = lb/in           |
| N/mm <sup>2</sup> x 145 = psi |
| MPa x 145 = psi               |
| N·m x 8.851 = lb·in           |
| N·m x 0.738 = lb·ft           |
| N·mm x 0.142 = oz·in          |
| mPa·s = cP                    |

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:**

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

**In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:**

The information provided in this Technical Data Sheet (TDS) including the

recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**In case products are delivered by Henkel Corporation, or Henkel Canada Corporation, the following disclaimer is applicable:**

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

**Trademark usage**

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 1.2

