



## HAD 4-S



### Herdanschlussdose HAD 4-S Anwendung Auf- und Unterputz, IP 20

- Schraubenlose Klemmstellen bis 6 mm<sup>2</sup> Rundleiter
- P-FIX – schwenkbare Zugentlastung (Lieferzustand offen)
- Doppel-Kabelabgang (5 × 2,5 mm<sup>2</sup>, 3 × 4 mm<sup>2</sup>)
- Schnappdeckel

### connection box HAD 4-S surface und flush mounting, IP 20

- screwless terminals rated 6 mm<sup>2</sup> solid
- P-FIX – hinged strain relief (delivered open)
- two-way cable outlet (5 × 2,5 mm<sup>2</sup>, 3 × 4 mm<sup>2</sup>)
- snap-on cover

### boîtes de raccordement HAD 4-S montage saillie et encastré, IP 20

- bornes sans vis jusqu' à 6 mm<sup>2</sup> rigide
- P-FIX – serre-câble pivotant (ouvert à la livraison)
- double sortie de câble (5 × 2,5 mm<sup>2</sup>, 3 × 4 mm<sup>2</sup>)
- couvercle clipsé

Produktbezeichnung description description du produit	Artikel-Nr. code no. N° article	VPE p. u. unité	Querschnitt cross section section
HAD 4-S	304 01 24	20	5 × 2,5 mm <sup>2</sup> , 3 × 4 mm <sup>2</sup>