

## GYSMI 130P


- Welding unit with inverter technology piloted by microprocessor.
- The arc dynamic of the product is unique and revolutionary on the market.
- Can be used with all types of electrodes: rutile, basic, stainless steel, cast iron in direct current.
- Very handy, thanks to its small weight (2.9 kg), its highly reduced volume and its very low consumption.

### • MMA


- ✓ Immediate start thanks to its very high no-load voltage
- ✓ Constant welding power
- ✓ Very smooth melting due to the direct current.
- ✓ Insensate to supply current fluctuations or to the arc length.
- ✓ Very good penetration and perfect arc stability.

### • ASSETS

- ✓ **ARC FORCE** : punctual increase of current in difficult welding situation.
- ✓ **HOT START** : increased power at start
- ✓ **ANTI STICKING** : anti sticking process.



## LCD TECHNO 11

 **High quality LCD:** UV/IR DIN 15 protection  
Field of vision : 98 x 35 mm

 **Total weight:** 400 g

 **Power supply:** Solar

### Filter:

- Initial shade : 3
- Welding shade: 11
- Arcing reaction time  $\leq 0.6$  ms
- Ideal for MMA/MIG-MAG/TIG : from 10 to 200 A



Ref. 031449

Delivered in bundle with:  
· Earth cable (1,6m/ø16mm<sup>2</sup>)  
· Electrode holder (2m/ø16mm<sup>2</sup>)  
· Techno 11 TRUE COLOR helmet



Ref. 029972

Delivered in suitcase with:  
· Earth cable (1,6m/ø16mm<sup>2</sup>)  
· Electrode holder (2m/ø16mm<sup>2</sup>)

50/60hz	AM	I <sub>2</sub>	min>max	Ø1.6	Ø2	Ø2.5	Ø3.2	Ø4	Ø5	EN60974-1 (40°C)	U <sub>0</sub>	cm/kg	Protected & compatible POWER GENERATOR (+/- 15%)
										I <sub>A</sub> (60%)	X% (I <sub>2</sub> max)		
230V 1~	13A	10-130A	20-200A	62	50	47	24	-	-	45A	5%	80V 10x17x25 2.9	4 kW 5.0 kVA