



## PX 4 pH / mV (REDOX) / °C



### Produktmerkmale

- pH Messbereich: -2...16 pH, Auflösung 0,01 pH
- mV Funktion für pH Elektroden Qualitätstest
- REDOX Messbereich: -1000mV...+1900mV
- 1...3 Kalibrierpunkte
- interner Temperatursensor 0...60°C

5040-0247

### Product features

- pH scale: -2...16 pH, Resolution 0.01 pH
- mV function for pH electrode quality test
- REDOX measuring range:-1000mV...+1900mV
- 1...3 Calibration points
- internal temperature sensor 0 ... 60°C

## COND 5 Cond / TDS / Salzgehalt / Salinity / °C



### Produktmerkmale

- Leitfähigkeit Messbereich: 0,01µS...199,9mS
- TDS Messbereich: 0,01 ppm...199,9 ppt
- Salzgehalt: 0,1...100,0g/L
- Referenztemperatur 20/25°C wählbar (COND)
- 1...3 Kalibrierpunkte
- interner Temperatursensor 0...60°C

5040-0244

### Product features

- COND range: 0,01µS...199,9mS
- TDS range: 0,01 ppm...199,9 ppt
- Salinity: 0,1...100,0g/L
- Reference temperature 20/25 °C user selectable
- 1...3 Calibration points
- internal temperature sensor 0 ... 60°C

## PC 5 pH / Cond / TDS / Salzgehalt / Salinity / °C



### Produktmerkmale

- pH Messbereich: -2...16 pH, Auflösung 0.01 pH
- mV Funktion für pH Elektroden Qualitätstest
- Salzgehalt: 0,1...100,0g/L
- Leitfähigkeit Messbereich: 0,01µS...199,9mS
- Referenztemperatur 20/25°C wählbar (COND)
- 1...3 Kalibrierpunkte
- interner Temperatursensor 0...60°C

5040-0245

### Product features

- pH scale: -2...16 pH, Resolution 0.01 pH
- mV function for pH electrode quality test
- Salinity: 0,1...100,0g/L
- COND scale: 0,01µS...199,9mS
- Reference temperature 20/25 °C user selectable
- 1...3 Calibration points
- internal temperature sensor 0 ... 60°C

## PC 6 pH / mV (REDOX) / Cond / TDS / Salzgehalt / Salinity / °C



### Produktmerkmale

- pH Messbereich: -2...16 pH, Auflösung 0,01 pH
- mV Funktion für pH Elektroden Qualitätstest
- Salzgehalt: 0,1...100,0g/L
- REDOX Messbereich: -1000mV...+1900mV
- Leitfähigkeit Messbereich: 0,01µS...199,9mS
- Referenztemperatur 20/25°C wählbar (COND)
- 1...3 Kalibrierpunkte
- interner Temperatursensor 0...60°C

5040-0248

### Product features

- pH scale: -2...16 pH, Resolution 0.01 pH
- mV function for pH electrode quality test
- Salinity: 0.1...100.0g/L
- REDOX measuring range: -1000mV...+1900mV
- COND scale: 0.01µS...199.9mS
- Reference temperature 20/25°C user selectable
- 1...3 Calibration points
- internal temperature sensor 0 ... 60°C