

BUBI LF is a top quality, solvent-free prime coat for optimizing the adherence of all acrylate, butyl, bitumen and caoutchouc adhesive tapes. It can be applied on all absorptive, mineral surfaces like plaster, concrete, cement plaster, aerated concrete, tile and lime sand brickwork with smoothed joints as well as on wood and wood composites. Also applicable without problems on polystyrene, EPS, XPS and so on.

BUBI LF primer is self-adhesive and resistant to water and thermal distortion. BUBI LF is NOT suitable for ORBIT-SYSTEM.

Technical Data

Composition:	watery acrylate-polymer dispersion, solvent free
Film property:	elastic
Processing temperature:	from +5°C
Drying time:	15 to 40 minutes
Consumption:	from 100g/m ²
Shelf life:	ca. 12 months unopened
Storage:	cool and dry, unopened. No direct sunlight.

Vorteile:

- strong increase of bonding courses
- creates adherent film
- self-adhesive
- cold workable from -10°C (air and material)

Important: A clean, dust-free, dry, ice-free surface around the area to be glued is a pre-condition for accurate adhesion. Stir well before using BUBI LF primer. Apply evenly with a paintroll or brush and let dry (porous surfaces need to be covered twice). Mind an even application. Before pressing the adhesive tape allow the primer to evaporate until it is transparent. Thickened primers can be diluted with water.

EISEDICHT Luftdichtungsmanschetten

Behrenstr. 3 • D-31737 Rinteln

Tel.: +49 (0) 5751 - 92 15 67 -30 www.eisedicht.de

Fax: +49 (0) 5751 - 92 15 67 -90 info@eisedicht.de

