



Costruttore/Manufacturer/Hersteller/Fabricant:

T.M.L. SRL
64010 CIVITELLA DEL TRONTO (TE) - ITALY
Tel +39 0861 927003 - web: www.tmlgroup.it

IT Dati Tecnici

Direttiva 2009/125/CE, Regolamento Delegato (UE) N° 812/2013, Regolamento (UE) N° 814/2013, EN 15332:2007, Direttiva PED 97/23/CE.

Mod./Art.: **PC01500F**
Classe energetica: **C**
Dispersione termica (S): **168.6 W**
Volume utile: **1472.9 L**
Isolamento: **Poliestere**

Descrizione Articolo:

Termoaccumulo per lo stoccaggio di acqua da riscaldamento prodotta da sorgenti di calore continue e discontinue; produzione di acqua calda sanitaria a mezzo di boiler interno in acciaio al carbonio vetroporcellanato (tank in tank). (DIN 4753.3)

EN Technical Data

Directive 2009/125 / EC, Regulation Officer (EU) No. 812/2013, Regulation (EU) N°814/2013, EN 15332: 2007, P.E.D. Directive 97/23 / EC.

Mod./Art.: **PC01500F**
Energy efficiency class: **C**
Heat loss (S): **168.6 W**
Effective Volume: **1472.9 L**
Insulation: **Polyester**

Product Description:

Thermal accumulator for the storage of heating water produced by continuous and discontinuous heat sources; production of domestic hot water by means of an enamelled (DIN 4753.3) carbon steel internal accumulator (in tank in tank).

DE Technische Daten

Richtlinie 2009/125/EG, Delegierte Verordnung (EU) Nr. 812/2013, Verordnung (EU) Nr. 814/2013, EN 15332:2007, Verordnung P.E.D. 97/23/EG

Mod./Art.: **PC01500F**
Energieeffizienzklasse: **C**
Wärmeverlust (S): **168.6 W**
Nutzbares Volumen: **1472.9 L**
Isolierung: **Polyester**

Artikelbeschreibung:

Thermospeicher für Warmwasser-Speicherung aus kontinuierlichen und diskontinuierlichen Heizquellen. Die WW-Produktion erfolgt mittels eines integrierten, emaillierten (DIN 4753.3) Karbonstahl-Akkumulators (tank in tank).

FR Données Techniques

Directive 2009/125/CE, règlement délégué (CE) n°812/2013, règlement (CE) n°814/2013, EN15332:2007, Directive DESP 97/23/CE

Mod./Art.: **PC01500F**
Classe énergétique: **C**
Constante de refroidissement (S): **168.6 W**
Volume Utile: **1472.9 L**
Isolation: **Polyester**

Description du produit: