



CERT

DVGW type examination certificate

DVGW-Baumusterprüfzertifikat

DG-8531BP0364

Registration Number
Registriernummer

Field of Application <i>Anwendungsbereich</i>	products of gas supply <i>Produkte der Gasversorgung</i>
Owner of Certificate <i>Zertifikatinhaber</i>	Eurotubi Europa S.R.L. Via Croce Rossa Italiana, 12, I-20833 Nova Milanese (MI)
Distributor <i>Vertreiber</i>	Eurotubi Europa S.R.L. Via Croce Rossa Italiana, 12, I-20833 Nova Milanese (MI)
Product Category <i>Produktart</i>	installation systems and system joints: compression joint for metallic gas pipes (8531)
Product Description <i>Produktbezeichnung</i>	compression joint made of stainless steel for pipes made of stainless steel according to DVGW-GW 541
Model <i>Modell</i>	EUROTUBI Pressfitting Gas
Test Reports <i>Prüfberichte</i>	laboratory control test: 120001553-15 from 11.11.2015 (MPM)
Test Basis <i>Prüfgrundlagen</i>	DVGW G 5614 (01.12.2013)

70028-04-A-BE

Date of Expiry / File No. 26.07.2019 / 16-0220-GNV
Ablaufdatum / Aktenzeichen

28.06.2016 Rie A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 for certification of products for energy and water supply industry.

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte Stelle für die Zertifizierung von Produkten der Energie- und Wasserversorgung.



Deutsche
Akkreditierungsstelle
D-ZE-16028-01-05

DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

Gas Category <i>Gasart</i>	Remarks <i>Bemerkungen</i>
fuel gases according to G260	

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
EUROTUBI Pressfitting Gas	nominal pressure rating: PN 5/GT 5 nominal diameter: 15 mm	
EUROTUBI Pressfitting Gas	nominal pressure rating: PN 5/GT 5 nominal diameter: 18 mm	
EUROTUBI Pressfitting Gas	nominal pressure rating: PN 5/GT 5 nominal diameter: 22 mm	
EUROTUBI Pressfitting Gas	nominal pressure rating: PN 5/GT 5 nominal diameter: 28 mm	
EUROTUBI Pressfitting Gas	nominal pressure rating: PN 5/GT 5 nominal diameter: 35 mm	
EUROTUBI Pressfitting Gas	nominal pressure rating: PN 5/GT 5 nominal diameter: 42 mm	
EUROTUBI Pressfitting Gas	nominal pressure rating: PN 5/GT 5 nominal diameter: 54 mm	
EUROTUBI Pressfitting Gas	nominal pressure rating: PN 5/GT 5 nominal diameter: 76,1 mm	
EUROTUBI Pressfitting Gas	nominal pressure rating: PN 5/GT 5 nominal diameter: 88,9 mm	
EUROTUBI Pressfitting Gas	nominal pressure rating: PN 5/GT 5 nominal diameter: 108 mm	

certified Components**zertifizierte Bauteile / Werkstoffe**

Registr. No. <i>Registrier-Nr.</i>	Component <i>Bauteil (Produktart)</i>	Model/Type <i>Modell/Typ</i>	Manufacturer <i>Hersteller</i>
NG-5112BT0220	Sealing material made of elastomers for HN 136/HN 136 gas appliances		NOVOTEMA S.p.A.
NG-5112CL0298	Sealing material made of elastomers for TEC H16 GI-70 giallo/TEC gas appliances	H16 GI-70 giallo	Tecnogomma International S.p.A.

Hints of Utilization / Remarks**Verwendungshinweise / Bemerkungen**

Pressing tool: model "novopress" with pressing jaw model "novopress" (for dimensions 15...54 mm) respectively model "Klauke UAP 100" with pressing jaw model "Klauke" (for dimensions 76,1...108 mm).

Permitted ambient temperature range: -20...+70 °C

The requirements of the higher thermal resistance (HTB) are fulfilled up to nominal pressure rating PN 5/GT 5.

