

RAL-Lacquer

LOS 5020 ff.

Description:

- Fast and haddrying
- Polishingable after approx. 48 hours
- For lacquer repairs inside and outside
- Light-genuine and yellowness-free / weather-resistant
- High surface hardness, scratching and impact resistant
- After 30 minutes grip-firm, after approx. 2 hours dry

Characteristic:

High-quality acryl lacquer without FCKW

Application

Clean and grind the underground of rust, fat and dirt. Those surface which need not painted masking with tape! Vibrate the can approx. 3 minutes. Sample-spray / (test lacquer compatibility in inconspicuous place). Spraying distance approx. 25 cm. Spray several thin layers. Dust drying after 10 minutes, dry after approx. 24 hours. Not apply on synthetic resin.

Technische Daten

Form:	Aerosol
Colour:	Different
Odour:	Characteristic
Density (20°C):	0.81261 g/cm ³
Ignition point:	200°C
Flash point:	-97°C
Vapour pressure (20°C):	8300 hPa
Solubility in water:	not soluble or different to mix

Suggestions, processing and use of our products correspond to the best knowledge at printing of this leaflet and are always given without obligation. You only can serve as a clue in consideration of the changing conditions; from this no liabilities, liability and guarantee claims can be derived. Own tests must be carried out before application. Every manufacturer of our products is liable for the retention everything legal to regulations.