

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 25.09.2023

Version: 11.00 (replaces version 10.00)

Revision: 04.05.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Trade name:** SONAX SX 90 PLUS**Article number:**

04745050, 04749000

UFI: SEJ3-20DV-G00N-HDY7**1.2 Relevant identified uses of the substance or mixture and uses advised against****Application of the substance / the mixture**

Penetrating oil

Anticorrosion additive

Lubricant

Consumer uses: Private households / general public / consumers

Professional uses

Uses advised against None**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk**1.4 Emergency telephone number:****European Union:** +49 (0) 89 19240 (Poison Centre Munich)**United Kingdom:** 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

Eye Irrit. 2 H319 Causes serious eye irritation.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms

GHS07 GHS08

Signal word Danger**Hazard-determining components of labelling:**

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

White mineral oil, petroleum

Hazard statements

H319 Causes serious eye irritation.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P101

If medical advice is needed, have product container or label at hand.

(Contd. on page 2)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2023

Version: 11.00 (replaces version 10.00)

Revision: 04.05.2023

Trade name: SONAX SX 90 PLUS

(Contd. of page 1)

P102 Keep out of reach of children.
 P280 Wear eye protection.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P331 Do NOT induce vomiting.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards
Results of PBT and vPvB assessment
PBT:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

Determination of endocrine-disrupting properties

The substance/this mixture contains components that exhibit or are suspected of exhibiting endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1% or more.

CAS: 128-37-0	2,6-di-tert-butyl-p-cresol	List II
---------------	----------------------------	---------

SECTION 3: Composition/information on ingredients

3.2 Mixtures
Description: Formulation of mineral oil with additives in petroleum distillate

Dangerous components:

EC No 926-141-6 Reg.nr.: 01-2119456620-43-xxxx	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics Alternative CAS number: 64742-47-8 ⚠ Asp. Tox. 1, H304, EUH066	25-<50%
CAS: 8042-47-5 EINECS: 232-455-8 Reg.nr.: 01-2119487078-27-xxxx	White mineral oil, petroleum ⚠ Asp. Tox. 1, H304	25-<50%
CAS: 1474044-79-5 EC No 939-717-7 Reg.nr.: 01-2119980985-16-xxxx	calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate) Alternative CAS number: 57855-77-3 ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319	1-<3%
CAS: 110-25-8 EC number: 701-177-3 Reg.nr.: 01-2119488991-20-xxxx	(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine ⚠ Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400 (M=1); ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Aquatic Chronic 3, H412	1-<3%
CAS: 128-37-0 EINECS: 204-881-4 Reg.nr.: 01-2119565113-46-xxxx	2,6-di-tert-butyl-p-cresol ⚠ Aquatic Acute 1, H400 (M=1); Aquatic Chronic 1, H410 (M=1)	<0.25%

Regulation (EC) No 648/2004 on detergents / Labelling for contents

aliphatic hydrocarbons	≥30%
------------------------	------

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures
General information:

Take affected persons out into the fresh air.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 25.09.2023

Version: 11.00 (replaces version 10.00)

Revision: 04.05.2023

Trade name: SONAX SX 90 PLUS

(Contd. of page 2)

*Remove soiled clothing***After inhalation:***Supply fresh air.**In the event of irritation of the respiratory tract, dizziness, nausea or unconsciousness, call medical assistance immediately .***After skin contact:***Wash the areas of skin affected with water and a mild detergent.**If symptoms persist consult doctor.***After eye contact:***Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.***After swallowing:** *Do not induce vomiting; call for medical help immediately.***4.2 Most important symptoms and effects, both acute and delayed***Eye irritation**Coughing**Breathing difficulty**Headache**Nausea**Unconsciousness**Reddening, drying and crack formation of the skin***4.3 Indication of any immediate medical attention and special treatment needed***If swallowed or in case of vomiting, danger of entering the lungs.**Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.***SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents:***Water haze**Foam**Fire-extinguishing powder**Carbon dioxide***5.2 Special hazards arising from the substance or mixture***In case of fire, the following can be released:**Carbon monoxide (CO)**Carbon dioxide (CO₂)***5.3 Advice for firefighters****Protective equipment:***Do not inhale explosion gases or combustion gases.**Wear fully protective suit.**Do not enter the hazardous area without a self-contained breathing apparatus.**See Section 8 for information on personal protection equipment.***Additional information***Cool endangered receptacles with water spray.**Collect contaminated fire fighting water separately. It must not enter the sewage system.***SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures** *Ensure adequate ventilation***For non-emergency personnel***Do not inhale gases / fumes / aerosols.**The usual precautionary measures are to be adhered to when handling chemicals.***For emergency responders** *Wear protective equipment. Keep unprotected persons away.***6.2 Environmental precautions:***Do not allow to penetrate the ground/soil.**Do not allow to enter sewers/ surface or ground water.***6.3 Methods and material for containment and cleaning up:***Ensure adequate ventilation.**Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).**Dispose contaminated material as waste according to section 13.*

(Contd. on page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2023

Version: 11.00 (replaces version 10.00)

Revision: 04.05.2023

Trade name: SONAX SX 90 PLUS

(Contd. of page 3)

6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.
When using product on electrical parts disconnect them from power supply first. Before re-assembly, let dry for 2 minutes.

Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Provide solvent resistant, sealed floor.

Information about storage in one common storage facility:

Store away from foodstuffs.
Observe local/state/federal regulations.
Further information about storage conditions:
Store receptacle in a well ventilated area.
Keep container tightly sealed.
Recommended storage temperature: 20 °C.
Protect from heat and direct sunlight.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

RCP-TWA (EU)	Long-term value: 1200 mg/m ³ , 165 ppm Vapour / Total Hydrocarbons
--------------	--

CAS: 128-37-0 2,6-di-tert-butyl-p-cresol

WEL (Great Britain)	Long-term value: 10 mg/m ³
---------------------	---------------------------------------

Regulatory information WEL (Great Britain): EH40/2018

DNELs

CAS: 8042-47-5 White mineral oil, petroleum

Oral	DNEL	40 mg/kg (consumer) (long-term exposure - systemic effects)
Dermal	DNEL	92 mg/kg bw/day (consumer) (long-term exposure - systemic effects)
		220 mg/kg bw/day (worker) (long-term exposure - systemic effects)
Inhalative	DNEL	35 mg/m ³ (consumer) (long-term exposure - systemic effects)
	DNEL	160 mg/m ³ (worker) (long-term exposure - systemic effects)

CAS: 1474044-79-5 calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)

Dermal	DNEL	10 mg/kg (worker) (longterm systematic effects)
Inhalative	DNEL	5 mg/m ³ (worker) (longterm systematic effects)

CAS: 110-25-8 (Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine

Oral	DNEL	92 mg/kg (consumer) (acute systematic effects)
	DNEL	5 mg/kg (consumer) (longterm systematic effects)
Dermal	DNEL	50 mg/kg (consumer) (acute systematic effects)
		10 mg/kg (worker) (longterm systematic effects)
	DNEL	5 mg/kg (consumer) (longterm systematic effects)
Inhalative		100 mg/kg (worker) (acute systematic effects)
	DNEL	9 mg/m ³ (consumer) (acute locale effects)
		18 mg/m ³ (worker) (acute locale effects)

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 25.09.2023

Version: 11.00 (replaces version 10.00)

Revision: 04.05.2023

Trade name: SONAX SX 90 PLUS

(Contd. of page 4)

	DNEL	0.005 mg/m ³ (consumer) (longterm local effects) 0.01 mg/m ³ (worker) (longterm local effects)
	DNEL	0.1 mg/m ³ (consumer) (longterm systematic effects) 0.2 mg/m ³ (worker) (longterm systematic effects)
CAS: 128-37-0 2,6-di-tert-butyl-p-cresol		
Oral	DNEL	0.25 mg/kg bw/day (vls)
Dermal	DNEL	0.25 mg/kg (vls) 0.5 mg/kg (wls)
Inhalative	DNEL	0.435 mg/m ³ (vls) 1.76 mg/m ³ (wls)
PNECs		
CAS: 1474044-79-5 calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)		
Oral	PNEC	22.2 mg/kg food (human)
	PNEC	10 mg/l (KS) 0.004 mg/l (water (fresh water)) 0.0004 mg/l (water (sea water))
	PNEC	69 mg/kg (sediment (fresh water)) 6.9 mg/kg (sediment (sea water)) 13.9 mg/kg (soil)
CAS: 110-25-8 (Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine		
	PNEC	0.0043 mg/l (sporadic release) 0.00043 mg/l (water (fresh water)) 0.000043 mg/l (water (sea water))
CAS: 128-37-0 2,6-di-tert-butyl-p-cresol		
	PNEC	0.017 mg/l (sewage plant) 0.0002 mg/l (freshwater (Süßwasser)) 0.00002 mg/l (sediment (sea water))
	PNEC	0.054 mg/kg (gro) 0.458 mg/kg (sediment (fresh water)) 0.046 mg/kg (sediment (sea water))

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls**Suitable technical control devices**

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Individual protection measures, such as personal protective equipment**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Respiratory protection:

If the occupational exposure limit is exceeded:

The following breathing protection is recommended:

Respiratory filter for organic gases and vapours (Type A)

Identification colour: Brown

[DIN EN 14387]

Hand protection Protective gloves

Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

[EN 374]

Penetration time of glove material Value for the permeation: Level 6 (≥480min)

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 25.09.2023

Version: 11.00 (replaces version 10.00)

Revision: 04.05.2023

Trade name: SONAX SX 90 PLUS

Eye/face protection

Safety glasses
[EN 166]

(Contd. of page 5)

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****General Information****Physical state**

Fluid

Colour:

Brown

Odour:

Solvent-like

Melting point/freezing point:

Undetermined.

Boiling point or initial boiling point and boiling range

180-270 °C (Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics)

Flammability

Combustible liquid.

Lower and upper explosion limit**Lower:**

0.6 Vol % (Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics)

Upper:

7 Vol % (Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics)

Flash point:

85 °C (DIN 51758)

Decomposition temperature:

Not determined.

pH

Not applicable.

Viscosity:**Kinematic viscosity at 40 °C**<20.5 mm²/s**Solubility****water:**

Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)

Not determined.

Vapour pressure at 20 °C:

<1 hPa (Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics)

Density and/or relative density**Density at 20 °C:**0.83-0.85 g/cm³**Vapour density**

Not determined.

9.2 Other information**Appearance:****Form:**

Fluid

Important information on protection of health and environment, and on safety.**Ignition temperature:**

Not determined.

Explosive properties:

Not determined.

Change in condition**Evaporation rate**

Not applicable.

Information with regard to physical hazard classes**Explosives**

Void

Flammable gases

Void

Aerosols

Void

Oxidising gases

Void

Gases under pressure

Void

Flammable liquids

Void

Flammable solids

Void

Self-reactive substances and mixtures

Void

Pyrophoric liquids

Void

Pyrophoric solids

Void

Self-heating substances and mixtures

Void

Substances and mixtures, which emit flammable**gases in contact with water**

Void

Oxidising liquids

Void

Oxidising solids

Void

Organic peroxides

Void

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.09.2023

Version: 11.00 (replaces version 10.00)

Revision: 04.05.2023

Trade name: SONAX SX 90 PLUS

(Contd. of page 6)

Corrosive to metals
Desensitised explosives

Void
Void

SECTION 10: Stability and reactivity

10.1 Reactivity No dangerous reactions known.

10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

10.5 Incompatible materials: strong oxidizing agents

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/8h	>5,000 mg/m ³ (rat) (OECD 403)

CAS: 8042-47-5 White mineral oil, petroleum

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)

CAS: 1474044-79-5 calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)

Oral	LD50	>2,500 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)
Inhalative	LD50	>20 mg/l (rat)

CAS: 110-25-8 (Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine

Oral	LD50	5,000 mg/kg (rat) (OECD 401)
		>5,000 mg/kg (Ratte) (OECD 420)
Inhalative	LC50 / 4h	1.37 mg/m ³ (rat)
		1.8 mg/m ³ (Ratte) (OECD 403)

CAS: 128-37-0 2,6-di-tert-butyl-p-cresol

Oral	LD50	>5,000 mg/kg (rat) (OECD-Prüfrichtlinie 401)
Dermal	LD50	>2,000 mg/kg (rat) (OECD-Prüfrichtlinie 402)

Skin corrosion/irritation Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard

Viscosity: < 20,5mm²/s (40°C)

May be fatal if swallowed and enters airways.

(Contd. on page 8)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2023

Version: 11.00 (replaces version 10.00)

Revision: 04.05.2023

Trade name: SONAX SX 90 PLUS

(Contd. of page 7)

Additional toxicological information:

Repeated dose toxicity

Based on available data, the classification criteria are not met.

CAS: 1474044-79-5 calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)

Oral	NOAEL 90 d	100 mg/kg (rat) (OECD 408, 90d, target organ: liver)
------	------------	--

11.2 Information on other hazards

Endocrine disrupting properties

The product contains substances suspected of causing endocrine disruptions with health effects.

CAS: 128-37-0	2,6-di-tert-butyl-p-cresol
---------------	----------------------------

List II

SECTION 12: Ecological information

12.1 Toxicity There are no ecotoxicological data available on this mixture.

Aquatic toxicity:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

LLO 96 h	1,000 mg/l (Oncorhynchus mykiss)
ELO 48 h	1,000 mg/l (Daphnia magna)
ELO 72 h	1,000 mg/l (Pseudokirchneriella subcapitata)

CAS: 8042-47-5 White mineral oil, petroleum

NOELR	>100 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
LC50 / 96h	>1,000 mg/l (Leuciscus idus) (OECD 203)
EC50 / 48h	>100 mg/l (daphnia)
NOEC/NOEL	≥100 mg/l (fish) (96h)
	≥100 mg/l (algae) (72h)
	≥100 mg/l (daphnia) (48h)

CAS: 1474044-79-5 calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)

Inhalative	LC50/1	>20 mg/L (rat)
	LC50 / 96 h	>0.28 mg/l (fish)
	NOEL 21 d	2.2-10 mg/l (daphnia)
	EC50	>0.27 mg/l (daphnia)
	EC50 / 48h	>0.27 mg/l (daphnia)
	IC50 / 48h	>0.27 mg/l (daphnia)
	NOEC / 72 h	>0.27 mg/l (algae)

CAS: 110-25-8 (Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine

LC50 / 96 h	6.8 mg/l (fish)
EC20 / 0.5 h	50 mg/l (activated sludge)
EC50 / 48h	0.43 mg/l (Daphnia magna)
EC50 / 72h	6.3 mg/l (Scenedesmus subspicatus)
	0.91 mg/l (Desmodesmus subspicatus) (OECD 201)

CAS: 128-37-0 2,6-di-tert-butyl-p-cresol

LC50 / 96 h	0.758 mg/l (algae)
LC50 / 96h	0.199 mg/l (fish)
EC50 / 48h	0.48 mg/l (Daphnia magna)
NOEC / 21 d	0.053 mg/l (Oryzias latipes)
	0.069 mg/l (Daphnia magna)

12.2 Persistence and degradability

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Biodegradation	69 % (28d)
----------------	------------

CAS: 8042-47-5 White mineral oil, petroleum

Biodegradation	>60 % (28d (OECD 301B))
----------------	-------------------------

(Contd. on page 9)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2023

Version: 11.00 (replaces version 10.00)

Revision: 04.05.2023

Trade name: SONAX SX 90 PLUS

(Contd. of page 8)

CAS: 110-25-8 (Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine

CSB 2,400 mg/g

Biodegradation 85 % (OECD 301 B Ready Biodegradability -. CO2 Evolution)

12.3 Bioaccumulative potential

CAS: 1474044-79-5 calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)

BCF 3.16

log POW >6.6

CAS: 110-25-8 (Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine

log POW 3.5-4.2

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB

12.6 Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

12.7 Other adverse effects

Additional ecological information:

General notes:

The product may not be released into the environment without control.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste classified as hazardous according to Annex III to Directive 2008/98/EC.

Recommendation Waste must be disposed of while observing the local, official regulations.

European waste catalogue

1) Disposal / product

2) Disposal / contaminated packaging

20 01 13*	solvents
15 01 10*	packaging containing residues of or contaminated by hazardous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID/ADN, IMDG, IATA Void

14.2 UN proper shipping name

ADR/RID/ADN, IMDG, IATA Void

14.3 Transport hazard class(es)

ADR/RID/ADN, ADN, IMDG, IATA
Class Void

14.4 Packing group

ADR/RID/ADN, IMDG, IATA Void

14.5 Environmental hazards:

Marine pollutant: No

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 25.09.2023

Version: 11.00 (replaces version 10.00)

Revision: 04.05.2023

Trade name: SONAX SX 90 PLUS

(Contd. of page 9)

14.6 Special precautions for user	Not applicable.
--	-----------------

14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
---	-----------------

UN "Model Regulation":	Void
-------------------------------	------

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
European Directives:

Directive 2010/75/EU (VOC) 39.72 %

Catégorie SEVESO (DIRECTIVE 2012/18/EU) not subject to
REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS
--

None of the ingredients is listed.

National regulations:**Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Relevant phrases

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

Serious eye damage/irritation Aspiration hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
--	--

Date of previous version: 20.07.2022**Version number of previous version:** 10.00**Abbreviations and acronyms:**

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = letal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 25.09.2023

Version: 11.00 (replaces version 10.00)

Revision: 04.05.2023

Trade name: SONAX SX 90 PLUS

(Contd. of page 10)

*DNEL: Derived No-Effect Level (UK REACH)**PNEC: Predicted No-Effect Concentration (UK REACH)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**IOELV = indicative occupational exposure limit values**Acute Tox. 4: Acute toxicity – Category 4**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Dam. 1: Serious eye damage/eye irritation – Category 1**Eye Irrit. 2: Serious eye damage/eye irritation – Category 2**Asp. Tox. 1: Aspiration hazard – Category 1**Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1**Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3**** Data compared to the previous version altered.**

-GB-