

Page 1 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.07.2019 / 0016

Replacing version dated / version: 28.01.2019 / 0015

Valid from: 18.07.2019 PDF print date: 19.07.2019 Batterie-Pol-Fett-Spray 300 mL

Art.: 3141

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Batterie-Pol-Fett-Spray 300 mL

Art.: 3141

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Lubricant

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC24 - Lubricants, greases, release products

Process category [PROC]:

PROC 7 - Industrial spraying

PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC11 - Non industrial spraying

PROC20 - Use of functional fluids in small devices

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC 7 - Use of functional fluid at industrial site

ERC 8a - Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC 8d - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet



LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)
Hazard class Hazard category Hazard statement



Page 2 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.07.2019 / 0016

Replacing version dated / version: 28.01.2019 / 0015

Valid from: 18.07.2019 PDF print date: 19.07.2019 Batterie-Pol-Fett-Spray 300 mL

Art.: 3141

H315-Causes skin irritation. Skin Irrit. 2

Asp. Tox. 1 H304-May be fatal if swallowed and enters airways.

STOT SE 3 H336-May cause drowsiness or dizziness.

2 Aquatic Chronic H411-Toxic to aquatic life with long lasting effects.

Aerosol H222-Extremely flammable aerosol.

Aerosol H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H315-Causes skin irritation. H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves.

P312-Call a POISON CENTRE / doctor if you feel unwell.

P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501-Dispose of contents / container to an approved waste disposal facility.

Without adequate ventilation, formation of explosive mixtures may be possible.

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substance

n.a.

3.2 Mixture	
Hydrocarbons, C6, isoalkanes, <5% n-hexane	
Registration number (REACH)	01-2119484651-34-XXXX
Index	
EINECS, ELINCS, NLP	931-254-9 (REACH-IT List-No.)
CAS	(64742-49-0)
content %	25-50



Page 3 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.07.2019 / 0016

Replacing version dated / version: 28.01.2019 / 0015

Valid from: 18.07.2019 PDF print date: 19.07.2019 Batterie-Pol-Fett-Spray 300 mL

Art.: 3141

	Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315
		STOT SE 3, H336
l		Aquatic Chronic 2, H411

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
Registration number (REACH)	01-2119475514-35-XXXX
Index	
EINECS, ELINCS, NLP	921-024-6 (REACH-IT List-No.)
CAS	
content %	20-<25
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225
	Skin Irrit. 2, H315
	Asp. Tox. 1, H304
	STOT SE 3, H336
	Aquatic Chronic 2, H411

9-Octadecenoic acid (Z-), reaction products with triethanolamine, di-Me	
sulfate-quaternized	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	302-242-5
CAS	94095-35-9
content %	0,1-<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Irrit. 2, H319
	Skin Irrit. 2, H315

4,5-dihydro-2-heptadecyl-1H-imidazole-1-ethylamine	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	221-133-2
CAS	3010-23-9
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Corr. 1B, H314
	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 1, H410 (M=1)
	Eye Dam. 1, H318

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eve contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion



(B)

Page 4 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.07.2019 / 0016

Replacing version dated / version: 28.01.2019 / 0015

Valid from: 18.07.2019 PDF print date: 19.07.2019 Batterie-Pol-Fett-Spray 300 mL

Art.: 3141

Typically no exposure pathway.

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur: Irritation of the eyes

Irritation of the respiratory tract

Coughing Headaches Nausea

Effects/damages the central nervous system

Narcotic effect.

With long-term contact:

Product removes fat.

Dermatitis (skin inflammation)

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

CO2

Extinction powder

Sand

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Danger of bursting (explosion) when heated

Explosive vapour/air or gas/air mixtures.

In case of spreading near the ground, flashback to distance sources of ignition is possible.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous. If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:



Page 5 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.07.2019 / 0016

Replacing version dated / version: 28.01.2019 / 0015

Valid from: 18.07.2019 PDF print date: 19.07.2019 Batterie-Pol-Fett-Spray 300 mL

Art.: 3141

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

Do not wash away with water or watery cleaning agents.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Observe special regulations for aerosols!

Do not store with oxidizing agents.

Observe special storage conditions.

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

Chemical Name	Hydrocarbons, C6,	isoalkanes, <5% n-hexane			Content %:25-50
WEL-TWA: 800 mg/m3		WEL-STEL:			
Monitoring procedures:	- [9 Praeger - Hydrocarbons 2/a	581)		
	- [Praeger - Hydrocarbons 0,1%/c (81	1 03 571)		
	- (Compur - KITA-187 S (551 174)			
BMGV:			Other information: (O	EL acc. t	to RCP-method,
			paragraphs 84-87, EH4	10)	
® 0					Content %:20-
Chemical Name	Hydrocarbons, C6-	C7, n-alkanes, isoalkanes, cyclics	, <5% n-hexane		<25
WEL-TWA: 800 mg/m3		WEL-STEL:			
Monitoring procedures:	- (Compur - KITA-187 S (551 174)			
BMGV:			Other information: (O	EL acc. t	to RCP-method,
			paragraphs 84-87, EH4	10)	
Chemical Name	Isobutane				Content %:
WEL-TWA: 1000 ppm (EX) (ACGI		WEL-STEL:			3331tt 70.



®−

Page 6 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.07.2019 / 0016

Replacing version dated / version: 28.01.2019 / 0015

Valid from: 18.07.2019 PDF print date: 19.07.2019 Batterie-Pol-Fett-Spray 300 mL

Art.: 3141

Monitoring procedures:	-	Compur - KITA-1	113 SB(C) (549 36	8)		
BMGV:				Other information:	=	
Chemical Name	Butane					Content %:
		MEL OTEL	750 (1010	(0)		Content 70.
WEL-TWA: 600 ppm (1450 mg/m3)		750 ppm (1810 m	g/m3)		
Monitoring procedures:	-	Compur - KITA-2	221 SA (549 459)			
BMGV:				Other information:	•	
Chemical Name	Propane					Content %:
WEL-TWA: 1000 ppm (ACGIH)		WEL-STEL:				
Monitoring procedures:	-	Compur - KITA-1	125 SA (549 954)			
BMGV:				Other information:	•	
Chemical Name	Oil mist, mineral					Content %:
WEL-TWA: 5 mg/m3 (Mineral oil, e		WEL-STEL:				
working fluids, ACGIH)	· ·					
Monitoring procedures:	=	Draeger - Oil 10/			•	
	-	Draeger - Oil Mis	st 1/a (67 33 031)			
BMGV:		·		Other information:		

Hydrocarbons, C6, isoall	kanes, <5% n-hexane					
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	1301	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1377	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1131	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	13964	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5306	mg/m3	

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane									
Area of application	application Exposure route / Environmental compartment		Descriptor	Value	Unit	Note			
Consumer	Human - oral	Long term, systemic effects	DNEL	699	mg/kg bw/day				
Consumer	Human - dermal	Long term, systemic effects	DNEL	699	mg/kg bw/day				
Consumer	Human - inhalation	Long term, systemic effects	DNEL	608	mg/kg bw/day				
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	773	mg/kg bw/day				
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	2035	mg/kg bw/day				

<sup>WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW =
"Arbeitsplatzgrenzwert" (workplace limit value, Germany).</sup>

8.2 Exposure controls

8.2.1 Appropriate engineering controls

^{(8) =} Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

^{(8) =} Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

^{** =} The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.



(B)

Page 7 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.07.2019 / 0016

Replacing version dated / version: 28.01.2019 / 0015

Valid from: 18.07.2019 PDF print date: 19.07.2019 Batterie-Pol-Fett-Spray 300 mL

Art.: 3141

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Protective nitrile gloves (EN 374).

Minimum layer thickness in mm:

>= 0,4

Permeation time (penetration time) in minutes:

<= 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Aerosol. Active substance: liquid.

Colour: Orange
Odour threshold: Not determined



Page 8 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.07.2019 / 0016

Replacing version dated / version: 28.01.2019 / 0015

Valid from: 18.07.2019 PDF print date: 19.07.2019 Batterie-Pol-Fett-Spray 300 mL

Art.: 3141

pH-value: n.a.

Melting point/freezing point: Not determined

Initial boiling point and boiling range: n.a. Flash point: n.a. Evaporation rate: n.a. Flammability (solid, gas): n.a. Lower explosive limit: 1 Vol-% Upper explosive limit: 8.5 Vol-% 2400 hPa (20°C) Vapour pressure: Vapour density (air = 1): Not determined

Density: 0,65 g/cm3 (20°C, Active substance)

Bulk density:

n.a. Solubility(ies): Not determined Water solubility: Insoluble Partition coefficient (n-octanol/water): Not determined

>200 °C (Ignition temperature) Auto-ignition temperature: No

Auto-ignition temperature:

Decomposition temperature: Not determined

Viscosity:

Explosive properties: Product is not explosive. When using: development of explosive

vapour/air mixture possible.

Oxidising properties:

9.2 Other information

Miscibility: Not determined Fat solubility / solvent: Not determined Conductivity: Not determined Surface tension: Not determined

Solvents content: 88,23 %

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Pressure increase will result in danger of bursting.

Heating, open flame, ignition sources

10.5 Incompatible materials

Avoid contact with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Batterie-Pol-Fett-Spray 300 mL						
Art.: 3141						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						



Page 9 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.07.2019 / 0016

Replacing version dated / version: 28.01.2019 / 0015

Valid from: 18.07.2019 PDF print date: 19.07.2019 Batterie-Pol-Fett-Spray 300 mL Art.: 3141

Germ cell mutagenicity:		n.d.a.
Carcinogenicity:		negative, the
		real
		Naphthalene
		content is <1%
Reproductive toxicity:		n.d.a.
Specific target organ toxicity -		n.d.a.
single exposure (STOT-SE):		
Specific target organ toxicity -		n.d.a.
repeated exposure (STOT-RE):		
Aspiration hazard:		n.d.a.
Symptoms:		n.d.a.

Hydrocarbons, C6, isoalkanes	Hydrocarbons, C6, isoalkanes, <5% n-hexane								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes			
Acute toxicity, by oral route:	LD50	>16750	mg/kg	Rat	OECD 401 (Acute Oral				
					Toxicity)				
Acute toxicity, by dermal route:	LD50	>3350	mg/kg	Rabbit	OECD 402 (Acute				
					Dermal Toxicity)				
Acute toxicity, by inhalation:	LC50	259354	mg/m3	Rat	OECD 403 (Acute				
					Inhalation Toxicity)				
Skin corrosion/irritation:						Irritant			
Respiratory or skin				Mouse	OECD 429 (Skin	No (skin contact)			
sensitisation:					Sensitisation - Local				
					Lymph Node Assay)				
Aspiration hazard:						Yes			
Symptoms:						drowsiness,			
						unconsciousness			
						,			
						heart/circulatory			
						disorders,			
						headaches,			
						cramps,			
						drowsiness,			
						mucous			
						membrane			
						irritation,			
						dizziness,			
						nausea and			
						vomiting.			

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	
• • •					Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>20	mg/l/4h	Rat	OECD 403 (Acute	Vapours
					Inhalation Toxicity)	
Skin corrosion/irritation:						Product removes
						fat., Irritant
Skin corrosion/irritation:						Repeated
						exposure may
						cause skin
						dryness or
						cracking.
Serious eye damage/irritation:						Not irritant
Respiratory or skin						Not sensitizising
sensitisation:						
Specific target organ toxicity -						May cause
single exposure (STOT-SE):						respiratory
						irritation.
Aspiration hazard:						Yes



Page 10 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.07.2019 / 0016

Replacing version dated / version: 28.01.2019 / 0015

Valid from: 18.07.2019 PDF print date: 19.07.2019 Batterie-Pol-Fett-Spray 300 mL Art.: 3141

Symptoms:			drowsiness,
			unconsciousness
			,
			heart/circulatory
			disorders,
			headaches,
			cramps,
			drowsiness,
			mucous
			membrane
			irritation,
			dizziness,
			nausea and
			vomiting.,
			Chemical
			pneumonitis
			(condition similar
			to pneumonia)
•	 	l l	

4,5-dihydro-2-heptadecyl-1H-ir Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Skin corrosion/irritation:				Rabbit	Toxicity)	Irritant, Analogous conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Risk of serious damage to eyes., Analogous conclusion
Symptoms:						gastrointestinal disturbances
Experiences in humans:						Corrosive, Analogous conclusion

Isobutane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation Test)	
Aspiration hazard:						No
Symptoms:						unconsciousness
						, frostbite,
						headaches,
						cramps,
						dizziness,
						nausea and
						vomiting.

Butane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation Test)	
Aspiration hazard:						No



B.

Page 11 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.07.2019 / 0016

Replacing version dated / version: 28.01.2019 / 0015

Valid from: 18.07.2019 PDF print date: 19.07.2019 Batterie-Pol-Fett-Spray 300 mL Art.: 3141

Symptoms:		ataxia, breathing
		difficulties,
		drowsiness,
		unconsciousness
		, frostbite,
		disturbed heart
		rhythm,
		headaches,
		cramps,
		intoxication,
		dizziness,
		nausea and
		vomiting.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation Test)	
Reproductive toxicity	NOAEC	21,641	mg/l		OECD 422 (Combined	
(Developmental toxicity):					Repeated Dose Tox.	
					Study with the	
					Reproduction/Developm.	
					Tox. Screening Test)	
Aspiration hazard:						No
Symptoms:						breathing
						difficulties,
						unconsciousnes
						, frostbite,
						headaches,
						cramps, mucous
						membrane
						irritation,
						dizziness,
						nausea and
						vomiting.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							Product is
							slightly volatile.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Other adverse							n.d.a.
effects:							
Other information:							According to the
							recipe, contains
							no AOX.



(B)

Page 12 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.07.2019 / 0016

Replacing version dated / version: 28.01.2019 / 0015

Valid from: 18.07.2019 PDF print date: 19.07.2019 Batterie-Pol-Fett-Spray 300 mL

Art.: 3141

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	48h	>1	mg/l	Oryzias latipes		Analogous
							conclusion
12.1. Toxicity to fish:	NOEC/NOEL	28d	4,09	mg/l	Oncorhynchus	QSAR	
					mykiss		
12.1. Toxicity to daphnia:	EC50	48h	31,9	mg/l	Daphnia magna	QSAR	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	7,14	mg/l	Daphnia magna	QSAR	
12.1. Toxicity to daphnia:	LC50	48h	3,87	mg/l	Daphnia magna		Analogous
							conclusion
12.1. Toxicity to algae:	NOELR	72h	30	mg/l	Raphidocelis		
					subcapitata		
12.1. Toxicity to algae:	ErC50	72h	55	mg/l	Pseudokirchneriell		Analogous
					a subcapitata		conclusion
12.1. Toxicity to algae:	EC50	72h	13,56	mg/l	Pseudokirchneriell	QSAR	
					a subcapitata		
12.2. Persistence and		28d	98	%			Readily
degradability:							biodegradable
							(Analogous
							conclusion)
12.3. Bioaccumulative	Log Kow		4				
potential:							
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	11,4	mg/l	Leuciscus idus	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	NOELR	21d	1	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	3	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	30	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	81	%			Readily biodegradable, Analogous conclusion
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Other information:	AOX		0	%			
Other information:	DOC						DOC-elimination degree(complex ng organic substance)>= 80%/28d:, n.a.

4,5-dihydro-2-heptadecyl-1H-imidazole-1-ethylamine										
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes			
12.1. Toxicity to fish:	LC50	96h	0,35	mg/l		OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion			



B

Page 13 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.07.2019 / 0016

Replacing version dated / version: 28.01.2019 / 0015

Valid from: 18.07.2019 PDF print date: 19.07.2019 Batterie-Pol-Fett-Spray 300 mL

Art.: 3141

12.1. Toxicity to daphnia:	EC50	48h	0,29	mg/l	Daphnia magna	OECD 202	Analogous
						(Daphnia sp.	conclusion
						Acute	
						Immobilisation	
						Test)	
12.2. Persistence and						OECD 301	Not readily
degradability:						(Ready	biodegradable
						Biodegradability)	_
Other information:	COD		2704,00	mg/l		DIN 38409-H41	
			0				

Isobutane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative							A notable
potential:							biological
							accumulation
							potential is not to
							be expected
							(LogPow 1-3).
12.1. Toxicity to fish:	LC50	96h	27,98	mg/l			
12.1. Toxicity to algae:	EC50	96h	7,71	mg/l			
12.2. Persistence and							Readily
degradability:							biodegradable
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

Butane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)



Page 14 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.07.2019 / 0016

Replacing version dated / version: 28.01.2019 / 0015

Valid from: 18.07.2019 PDF print date: 19.07.2019 Batterie-Pol-Fett-Spray 300 mL

Art.: 3141

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations. Take full aerosol cans to problem waste collection. Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

15 01 04 metallic packaging

15 01 10 packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

General statements

14.1. UN number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Classification code:5F

LQ: 1 L
14.5. Environmental hazards: 1 L
environmentally hazardous

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

AEROSOLS (ISOHEXANES, HYDROCARBONS, C9-C12)

14.3. Transport hazard class(es):

14.4. Packing group:

EmS:

2.1

F-D, S-U

Marine Pollutant: Yes

14.5. Environmental hazards: environmentally hazardous

Transport by air (IATA)

14.2. UN proper shipping name:

Aerosols, flammable

14.3. Transport hazard class(es):
2.1
14.4. Packing group:

14.5. Environmental hazards:

Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Comply with trade association/occupational health regulations.









Page 15 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.07.2019 / 0016

Replacing version dated / version: 28.01.2019 / 0015

Valid from: 18.07.2019 PDF print date: 19.07.2019 Batterie-Pol-Fett-Spray 300 mL

Art.: 3141

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered

according to storage, handling etc.):

according to storage, nandling etc.).		
Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
		dangerous substances as	dangerous substances as
		referred to in Article 3(10) for the	referred to in Article 3(10) for the
		application of - Lower-tier	application of - Upper-tier
		requirements	requirements
E2		200	500
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

88,23 %

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

2

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation	Evaluation method used
(EC) No. 1272/2008 (CLP)	
Skin Irrit. 2, H315	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

Skin Irrit. — Skin irritation

Asp. Tox. — Aspiration hazard

STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Aerosol — Aerosols

Flam. Liq. — Flammable liquid

Eye Irrit. — Eye irritation



Page 16 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.07.2019 / 0016

Replacing version dated / version: 28.01.2019 / 0015

Valid from: 18.07.2019 PDF print date: 19.07.2019 Batterie-Pol-Fett-Spray 300 mL

Art.: 3141

Skin Corr. — Skin corrosion

Aquatic Acute — Hazardous to the aquatic environment - acute

Eye Dam. — Serious eye damage

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the

International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances

and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community
ECHA European Chemicals Agency
EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

etc. et cetera EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable n.av. not available n.c. not checked n.d.a. no data available

OECD Organisation for Economic Co-operation and Development

org. organic

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List

Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.



Page 17 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.07.2019 / 0016

Replacing version dated / version: 28.01.2019 / 0015

Valid from: 18.07.2019 PDF print date: 19.07.2019 Batterie-Pol-Fett-Spray 300 mL

Art.: 3141

Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International

Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern

Telephone

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

These statements were made by: Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

 $\ensuremath{\mathbb{G}}$ by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.