



## Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 11

LOCTITE SF 7100 known as Loctite 7100

SDS No. : 228588  
V001.0

Revision: 25.07.2017  
printing date: 02.07.2021  
Replaces version from: -

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE SF 7100 known as Loctite 7100

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:  
Leak Detector

#### 1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA  
Henkelstr. 67  
40589 Düsseldorf

Germany

Phone: +49 211 797 0  
Fax-no.: +49 211 798 2009

ua-productsafety.de@henkel.com

#### 1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (CLP):

Serious eye irritation Category 2

H319 Causes serious eye irritation.

H229 Pressurised container: May burst if heated. Category 3

#### 2.2. Label elements

##### Label elements (CLP):

##### Hazard pictogram:



Signal word: Warning

Hazard statement: H229 Pressurised container: May burst if heated.  
H319 Causes serious eye irritation.

- Precautionary statement:** P251 Do not pierce or burn, even after use.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.  
P102 Keep out of reach of children.
- Precautionary statement:** P337+P313 If eye irritation persists: Get medical advice/attention.  
**Response**

### 2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### General chemical description:

Leak Detector

#### Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Fatty alcohol ether C12, 5EO acetic acid 27306-90-7		2,5- < 3 %	Eye Dam. 1 H318
ammonia, aqueous solution 1336-21-6	215-647-6 01-2119488876-14	0,1- < 0,25 %	Met. Corr. 1 H290 Skin Corr. 1B H314 Aquatic Acute 1 H400 Aquatic Chronic 2 H411

For full text of the H - statements and other abbreviations see section 16 "Other information".

Substances without classification may have community workplace exposure limits available.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.

Seek medical advice.

### 4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

Prolonged or repeated contact may cause skin irritation.

**4.3. Indication of any immediate medical attention and special treatment needed**

See section: Description of first aid measures

## SECTION 5: Firefighting measures

**5.1. Extinguishing media**

**Suitable extinguishing media:**

Carbon dioxide, foam, powder

**Extinguishing media which must not be used for safety reasons:**

None known

**5.2. Special hazards arising from the substance or mixture**

Oxides of carbon, oxides of nitrogen, irritating organic vapors.

**5.3. Advice for firefighters**

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

**Additional information:**

In case of fire, keep containers cool with water spray.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid skin and eye contact.

Ensure adequate ventilation.

**6.2. Environmental precautions**

Do not let product enter drains.

**6.3. Methods and material for containment and cleaning up**

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

**6.4. Reference to other sections**

See advice in section 8

## SECTION 7: Handling and storage

**7.1. Precautions for safe handling**

Use only in well-ventilated areas.

Vapours should be extracted to avoid inhalation.

Keep away from sources of ignition - no smoking.

**Hygiene measures:**

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

**7.2. Conditions for safe storage, including any incompatibilities**

Store in a cool, well-ventilated place.

Keep away from heat and direct sunlight.

Refer to Technical Data Sheet

**7.3. Specific end use(s)**

Leak Detector

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational Exposure Limits**Valid for  
Germany

None

**Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
ammonia, aqueous solution 1336-21-6	aqua (freshwater)		0,001 mg/l				
ammonia, aqueous solution 1336-21-6	aqua (marine water)		0,001 mg/l				
ammonia, aqueous solution 1336-21-6	aqua (intermittent releases)		0,0068 mg/l				

**Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
ammonia, aqueous solution 1336-21-6	Workers	dermal	Acute/short term exposure - systemic effects		6,8 mg/kg	
ammonia, aqueous solution 1336-21-6	Workers	dermal	Long term exposure - systemic effects		6,8 mg/kg	
ammonia, aqueous solution 1336-21-6	Workers	Inhalation	Acute/short term exposure - systemic effects		47,6 mg/m <sup>3</sup>	
ammonia, aqueous solution 1336-21-6	Workers	Inhalation	Acute/short term exposure - local effects		36 mg/m <sup>3</sup>	
ammonia, aqueous solution 1336-21-6	Workers	Inhalation	Long term exposure - systemic effects		47,6 mg/m <sup>3</sup>	
ammonia, aqueous solution 1336-21-6	Workers	Inhalation	Long term exposure - local effects		14 mg/m <sup>3</sup>	
ammonia, aqueous solution 1336-21-6	General population	dermal	Acute/short term exposure - systemic effects		68 mg/kg	
ammonia, aqueous solution 1336-21-6	General population	dermal	Long term exposure - systemic effects		68 mg/kg	
ammonia, aqueous solution 1336-21-6	General population	Inhalation	Acute/short term exposure - systemic effects		23,8 mg/m <sup>3</sup>	
ammonia, aqueous solution 1336-21-6	General population	Inhalation	Acute/short term exposure - local effects		7,2 mg/m <sup>3</sup>	
ammonia, aqueous solution 1336-21-6	General population	Inhalation	Long term exposure - systemic effects		23,8 mg/m <sup>3</sup>	
ammonia, aqueous solution 1336-21-6	General population	Inhalation	Long term exposure - local effects		2,8 mg/m <sup>3</sup>	
ammonia, aqueous solution 1336-21-6	General population	oral	Acute/short term exposure - systemic effects		6,8 mg/kg	
ammonia, aqueous solution 1336-21-6	General population	oral	Long term exposure - systemic effects		6,8 mg/kg	

**Biological Exposure Indices:**  
None

**8.2. Exposure controls:**

Respiratory protection:

Use only in well-ventilated areas.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filtertype: AX

Filter type: P2

Hand protection:

The use of chemical resistant gloves such as Neoprene or Natural Rubber is recommended

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:  
Wear protective glasses.  
Protective eye equipment should conform to EN166.

Skin protection:  
Wear suitable protective clothing.  
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	liquid aerosol colourless
Odor	characteristic
Odour threshold	No data available / Not applicable
pH (20 °C (68 °F))	7,5
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	100 °C (212 °F)
Flash point	104 °C (219.2 °F)
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	
lower	2,6 % (V)
upper	12,6 % (V)
Vapour pressure (20 °C (68 °F))	23,0000000 hPa
Relative vapour density:	No data available / Not applicable
Density (20 °C (68 °F))	1,017 g/cm <sup>3</sup>
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative) (Solvent: Water)	Miscible
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

### 9.2. Other information

Ignition temperature 371 °C (699.8 °F)

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

None known

### 10.2. Chemical stability

Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

See section reactivity

**10.4. Conditions to avoid**

Stable

**10.5. Incompatible materials**

None if used properly.

**10.6. Hazardous decomposition products**

None known.

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****General toxicological information:**

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

**Oral toxicity:**

May cause irritation to the digestive tract.

**Skin irritation:**

Prolonged or repeated contact may cause skin irritation.

**Eye irritation:**

Causes serious eye irritation.

**Acute oral toxicity:**

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Fatty alcohol ether C12, 5EO acetic acid 27306-90-7	LD50	> 2.000 mg/kg	oral		rat	not specified

**Acute inhalative toxicity:**

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
---------------------------------	---------------	-------	-------------------------	------------------	---------	--------

**Acute dermal toxicity:**

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
---------------------------------	---------------	-------	-------------------------	------------------	---------	--------

**Skin corrosion/irritation:**

Hazardous components CAS-No.	Result	Exposure time	Species	Method
ammonia, aqueous solution 1336-21-6	corrosive		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

**Serious eye damage/irritation:**

Hazardous components CAS-No.	Result	Exposure time	Species	Method
ammonia, aqueous solution 1336-21-6	corrosive			not specified

**Respiratory or skin sensitization:**

Hazardous components CAS-No.	Result	Test type	Species	Method
ammonia, aqueous solution 1336-21-6	not sensitising	not specified	guinea pig	not specified

**Germ cell mutagenicity:**

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
ammonia, aqueous solution 1336-21-6	negative	bacterial reverse mutation assay (e.g Ames test)	not specified		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
ammonia, aqueous solution 1336-21-6	negative	not specified		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

**Carcinogenicity:**

Hazardous components CAS-No.	Result	Species	Sex	Exposure time Frequency of treatment	Route of application	Method
ammonia, aqueous solution 1336-21-6	not carcinogenic	rat		104 w daily	oral: unspecified	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

**Reproductive toxicity:**

Hazardous substances CAS-No.	Result / Classification	Species	Exposure time	Species	Method
ammonia, aqueous solution 1336-21-6	NOAEL P = 408 mg/kg	screening oral: unspecified		rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

**SECTION 12: Ecological information****General ecological information:**

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

**12.1. Toxicity****Ecotoxicity:**

Do not empty into drains / surface water / ground water.

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Fatty alcohol ether C12, 5EO acetic acid 27306-90-7	LC50	7,5 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
ammonia, aqueous solution 1336-21-6	LC50	0,16 - 1,1 mg/l	Fish	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	OECD Guideline 203 (Fish, Acute Toxicity Test)
	NOEC	< 0,048 mg/l	Fish	31 d	Channel catfish	OECD Guideline 215 (Fish, Juvenile Growth Test)
ammonia, aqueous solution 1336-21-6	EC50	25,4 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
ammonia, aqueous solution 1336-21-6	EC50	> 1.000 mg/l	Algae	72 h	Skeletonema costatum	ISO 10253 (Water quality)
	NOEC	1.000 mg/l	Algae	72 h	Skeletonema costatum	ISO 10253 (Water quality)
ammonia, aqueous solution 1336-21-6	NOEC	0,79 mg/l	chronic Daphnia	96 h	Daphnia magna	EPA OPPTS 850.1300 (Daphnid Chronic Toxicity Test)



**12.2. Persistence and degradability****Persistence and Biodegradability:**

Readily degradable.

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Fatty alcohol ether C12, 5EO acetic acid 27306-90-7	readily biodegradable	aerobic	> 60 %	OECD 301 A - F

**12.3. Bioaccumulative potential / 12.4. Mobility in soil****Mobility:**

No data available for the product.

**Bioaccumulative potential:**

No data available for the product.

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
ammonia, aqueous solution 1336-21-6	-1,14					EU Method A.8 (Partition Coefficient)

**12.5. Results of PBT and vPvB assessment**

Hazardous components CAS-No.	PBT/vPvB
ammonia, aqueous solution 1336-21-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

**12.6. Other adverse effects**

No data available.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods**

Product disposal:

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

Disposal must be made according to official regulations.

Waste code

14 06 03 Other solvents and solvent mixtures

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

**SECTION 14: Transport information****14.1. UN number**

ADR	1950
RID	1950
ADN	1950
IMDG	1950
IATA	1950

**14.2. UN proper shipping name**

ADR	AEROSOLS
RID	AEROSOLS
ADN	AEROSOLS
IMDG	AEROSOLS
IATA	Aerosols, non-flammable

**14.3. Transport hazard class(es)**

ADR	2.2
RID	2.2
ADN	2.2
IMDG	2.2
IATA	2.2

**14.4. Packing group**

ADR  
RID  
ADN  
IMDG  
IATA

**14.5. Environmental hazards**

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

**14.6. Special precautions for user**

ADR	not applicable Tunnelcode: (E)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC content 10 - 15 %  
(2010/75/EC)

**15.2. Chemical safety assessment**

A chemical safety assessment has not been carried out.

**National regulations/information (Germany):**

WGK: WGK = 1, slightly water endangering product. Classification according to the mixture rules in German VwVwS regulation annex 4 from 27.July 2005

Storage class according to TRGS 510: 2B

**SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H290 May be corrosive to metals.
- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.
- H400 Very toxic to aquatic life.
- H411 Toxic to aquatic life with long lasting effects.

**Further information:**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

**Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.**