

## FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Angle grinders

### L 21-6 230

Order no. 391.514



#### 2100 watt angle grinder, 230 mm

- Robust motor housing and gearbox housing. Stable and robust steel gearbox as well as a spindle bearing protected by a metal cap also increase reliability and durability
- Ergonomically designed and very slender motor housing provides optimum guidance and handling. An additional vibration damping ring between the motor housing and rear handle reduces the vibrations
- SoftVib handgrip for reduced vibration can be mounted in three positions.
- Rear shaft handle with soft padding for secure grip
- Switch: with lock-off / lock-on switch
- Restart protection after power interruption
- Soft-start: for a soft start without power overloading
- Spindle lock
- Tool-free adjustment of safety guard
- Cutting guard, optional accessory (oder no. 389.625)

Technical attributes	L 21-6 230
Max. disc diameter	230 mm
No load speed	6500 rpm
Power input	2100 watt
Power output	1250 watt
Tool fixture	M 14
Clamping neck Ø	64 mm
Weight	5,2 kg

Standard equipment
1 guard grinding 230 Ø
1 SoftVib handle
1 pin wrench BL 5
1 clamping flange
1 clamping nut M14