

revision 11.07.2019 (GB) Version 6.1

Keramik-Kettenöl-BikeCer-Spray

! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product Keramik-Kettenöl-BikeCer-Spray

1.2. Relevant identified uses of the substance or mixture and uses advised against Recommended intended purpose(s)

Protects against corrosion, is water resistant, creepy

1.3. Details of the supplier of the safety data sheet

Manufacturer F.W.Klever

Hauptstraße 20, D-84168 Aham

Phone +49 (0) 8744 96 99 10, Fax + 49 (0) 8744 96 99 96

E-Mail info@ballistol.de Internet www.ballistol.de

Advice Qualitätssicherung

Phone +49 (0) 8744 96 99 30 E-mail (competent person):

info@ballistol.de

1.4. Emergency telephone number

Emergency advice Dr.Zettler (Werktags von 8.00 Uhr bis 16.00 Uhr) oder

Giftnotrufzentrale 022819240 Phone +49 (0) 8744 96 99 30

This number is only available at office times.

Vergiftungsinformationszentrale der Gesundheit Österreich

GmbH +4314064343

Classification procedure

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard Statements

Aerosol 1 H222, H229
Eye Irrit. 2 H319

Hazard statements for physical hazards
H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Hazard statements for health hazards
H319 Causes serious eye irritation.

2.2. Label elements



revision 11.07.2019 (GB) Version 6.1

Keramik-Kettenöl-BikeCer-Spray

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]





GHS02

GHS07

Signal word

Danger

Hazard statements for physical hazards H222

Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Hazard statements for health hazards

Causes serious eye irritation.

Precautionary Statements

General

P102 Keep out of reach of children.

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P251 Do not pierce or burn, even after use.

Response

P305 + P351 + IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

P338 present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention. P337 + P313

Storage

P410 + P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C/122°F.

Disposal

P501 Dispose of contents/container to recycling

2.3. Other hazards

No information available.

! SECTION 3: Composition/ information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

! Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
74-98-6	200-827-9	propane	4 - 6	Flam. Gas 1, H220 / Press. Gas
106-97-8	203-448-7	butane	10 - 15	Flam. Gas 1, H220 / Press. Gas
8008-20-6	232-366-4	Kerosine (petroleum); Straight run kerosine	5 - 10	Asp. Tox. 1, H304



revision 11.07.2019 (GB) Version 6.1

Keramik-Kettenöl-BikeCer-Spray

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.

In case of eye contact

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.

In case of ingestion

If swallowed by mistake drink plenty of water and seek medical treatment.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed Treatment (Advice to doctor)

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam

ABC-pulber

Carbon dioxide

Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In the event of fire the following can be released:

Lämmastikoksiidid (NOx)

Süsinikdioksiid (CO2)

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply (isolated).

Additional information

Cool endangered containers with water spray jet.

Heat causes increase in pressure and risk of bursting

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.



revision 11.07.2019 (GB) Version 6.1

Keramik-Kettenöl-BikeCer-Spray

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures For non-emergency personnel

Keep away sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.

High risk of slipping due to leakage/spillage of product.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

Clean contaminated objects and floor thoroughly under consideration of environment regulations.

Take up residues with absorbent material (e.g. sawdust).

6.4. Reference to other sections

No information available.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Do not spray into flames or ignition sources

General protective measures

Do not inhale gases/vapours/aerosols.

Hygiene measures

Remove soiled or soaked clothing immediately.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Protect aerosols from temperatures exceeding 50°C

7.2. Conditions for safe storage, including any incompatibilities Requirements for storage rooms and vessels

Keep only in original container.

Further information on storage conditions

Recommended storage temperature: room temperature.

Information on storage stability

Storage time: 3 years.

Storage group 2B

7.3. Specific end use(s)

No information available.



revision 11.07.2019 (GB) Version 6.1

Keramik-Kettenöl-BikeCer-Spray

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Respiratory protection

Respiratory protection must be worn whenever the WEL levels have been exceeded

The following applies to propane in general: If the concentration is exceeded, closed-circuit breathing apparatures must be used

Use filter apparatus type AX, identification colour brown according to EN 371

Hand protection

Gloves (oil-resistant)

Recommendation: protective glove (referred to EN374).

Eye protection

With demand: protective glasses

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance
aerosolColour
light yellowOdour
characteristic

Odour threshold

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	ca. 8				emulsioon vees
boiling point	-48 °C				(Propan)
Melting point / Freezing point	not determined				
Flash point	ca104 °C				(Propan)
Vapourisation rate	not determined				
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	not determined				
Self ignition temperature	not determined				
Lower explosion limit	ca. 1,5 Vol-%				(Propan)
Upper explosion limit	10,9 Vol-%				(Propan)
Vapour pressure	not determined				



revision 11.07.2019 (GB) Version 6.1

Keramik-Kettenöl-BikeCer-Spray

	Value	Temperature	at	Method	Remark
Relative density	ca. 0,874 g/ml	20 °C	1013 hPa		information concern to liquid phase
Vapour density	not determined				
Solubility in water		20 °C	1013 hPa		immiscible
Solubility/other	not determined				
Partition coefficient noctanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity kinematic	ca. 26				information concern to liquid phase
Oxidising properties No information available.					
Explosive properties No information available.					
9.2. Other information No information available.					

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Container under pressure. Protect from direct exposure to sunlight and temperatures exceeding 50°C.

10.5. Incompatible materials

Substances to avoid

Reactions with strong oxidising agents.

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Additional information

Product is stable under normal storage conditions



Moderately/partially biodegradable

revision 11.07.2019 (GB) Version 6.1

Keramik-Kettenöl-BikeCer-Spray

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	> 5000 mg/kg	rat		
LD50 acute dermal	> 5000 mg/kg	rabbit		
Eye irritation	low irritant			
Skin sensitization	non-sensitizing			

SECTION 12: Ecological information

12.1. Toxicity

No information available.

12.2. Persistence and degradability

Elimination rate	Method of analy	/sis	Method	Validation

Biological degradability

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste code No. Name of waste

13 02 05* mineral-based non-chlorinated engine, gear and lubricating oils

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Barrel: return by DSD (Dualistic System Germany)



revision 11.07.2019 (GB) Version 6.1

Keramik-Kettenöl-BikeCer-Spray

! SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1950	1950	1950
14.2. UN proper shipping name	Druckgaspackung	Aerosol (propane)	Aerosols flammable (propane)
14.3. Transport hazard class(es)	2	2	2.1
14.4. Packing group	-	-	-
14.5. Environmental hazards	No	No	No

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available.

Land and inland navigation transport ADR/RID

tunnel restriction code D Classification code 5F

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Water hazard class 1 self-classification

15.2. Chemical Safety Assessment

For this substance a chemical safety assessment is not required.

SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

Further information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 6.0

H220 Extremely flammable gas.

H304 May be fatal if swallowed and enters airways.