



**CARATTERISTICHE IDRAULICHE/ HYDRAULIC CHARACTERISTICS**

-Pressione nominale - Nominal pressure: 6 bar  
 -Limiti di temperatura del fluido - Fluid temperature limits: 0-110 °C

**MATERIALI/ MATERIALS**

- Corpo-Tubi/Body-Pipes Acciaio S235 Verniciato/Painted Steel S235
- Valvola automatica sfiato aria/Automatic air vent valve Ottone CW617N /Brass CW617N
- Defangatore/Dirt Remover Ottone CW617N/ Brass CW617N
- Isolamento/Insulation EPP/EPP
- Densità /Density 45 kg/mc
- Campo di temperatura/Working Temperature Range -5÷120 °C
- Conducibilità termica/Thermal Conductivity 0.037 W/(mk)
- Resistenza al fuoco/Reaction to fire (UL94) classe HBF/HBF class

SCALA SCALE 1:10	VALORI ANGOLARI ANGULAR VALUES				MATERIALE / MATERIAL	DISEGN. DRAW Dal Maso	DATA DATE 18/04/17
	fino > 3	≥ 3	> 30	> 120			
	a 3	a 6	a 120	a 1000			
	±0.15	±0.17	±0.25	±0.4			
TOLLERANZE DIMENSIONALI DIMENSIONAL TOLERANCES	PLASTICA PLASTIC	±0.15	±0.17	±0.25	±0.4	±1	±2.5
	METALLO METAL	±0.05	±0.05	±0.1	±0.15	±0.2	±0.3
	METALLO METAL	±0.1	±0.1	±0.2	±0.3	±0.5	±0.8
	METALLO METAL	±0.2	±0.3	±0.5	±0.8	±1.2	±2
 mut meccanica tovo MONTECCHIO MAGGIORE 36075 (VI) ITALY	COLLETTORE 2+1 (LATERALE) ATTACCHI PRINCIPALI G1 1/2				TRATT. TERMICO E/O SUPERF. HEAT/SUPERFICIAL TREATMENT VERNICIATO GRIGIO PP LU LF RAL7042	CORRISPONDE A/CORRESPONDS TO SOSTITUISCE I/SUBSTITUTES SOSTITUITO DA/SUBSTITUTED BY	
	ATTACCHI UTENZE GHIERE G1 1/2F INTERASSE 125mm						Referred to law terms, MUT SpA reserves the ownership on this drawing and prohibits to reproduction or communicate it without authorization. DISEGNO / DRAWING <b>7.030.02268-00</b> DIMENSIONI IN mm DIMENSIONS IN mm