

**Product information according to Commission Delegated Regulation (EU) 813/2013**

Product information is based on the average climate condition.

Model		WSYA050ML3	WGYA050ML3	WSYA080ML3	WGYA080ML3	WSYA080ML3	WGYA080ML3	WSYA100ML3	WGYA100ML3										
Outdoor unit		WOYA060KLT				WOYA080KLT				WOYA100KLT									
Air-to-water heat pump		Yes																	
Water-to-water heat pump		No																	
Brine-to-water heat pump		No																	
Low-temperature heat pump		No																	
Equipped with a supplementary heater		Yes																	
Heat pump combination heater		No***		Yes		No***		Yes		No***		Yes		No***		Yes			
Temperature application		°C	55	35	55	35	55	35	55	35	55	35	55	35	55	35	55	35	
Rated heat output (*)		P <sub>rated</sub>	kW	5	5	5	5	5	6	5	6	6	7	6	7	8	9	8	9
Seasonal space heating energy efficiency		η <sub>s</sub>	%	125	175	125	175	125	175	125	175	128	177	128	177	130	178	130	178
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>																			
T <sub>j</sub> = -7°C		P <sub>d,h</sub>	kW	4.2	4.4	4.2	4.4	4.7	5.0	4.7	5.0	5.5	5.8	5.5	5.8	7.3	7.5	7.3	7.5
T <sub>j</sub> = +2°C		P <sub>d,h</sub>	kW	2.5	2.7	2.5	2.7	2.9	3.0	2.9	3.0	3.3	3.5	3.3	3.5	4.4	4.6	4.4	4.6
T <sub>j</sub> = +7°C		P <sub>d,h</sub>	kW	1.9	2.1	1.9	2.1	1.8	2.1	1.8	2.1	2.1	2.3	2.1	2.3	3.6	3.9	3.6	3.9
T <sub>j</sub> = +12°C		P <sub>d,h</sub>	kW	2.3	2.4	2.3	2.4	2.3	2.4	2.3	2.4	2.4	2.5	2.4	2.5	4.3	4.4	4.3	4.4
T <sub>j</sub> = bivalent temperature		P <sub>d,h</sub>	kW	4.2	4.4	4.2	4.4	4.7	5.0	4.7	5.0	5.5	5.8	5.5	5.8	7.3	7.5	7.3	7.5
T <sub>j</sub> = operation limit temperature		P <sub>d,h</sub>	kW	3.8	4.0	3.8	4.0	4.0	4.5	4.0	4.5	5.0	5.6	5.0	5.6	7.1	7.3	7.1	7.3
T <sub>j</sub> = -15°C (if TOL < -20°C)		P <sub>d,h</sub>	kW	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Bivalent temperature		T <sub>biv</sub>	°C	-7	-7	-7	-7	-7	-7	-7	-7	-7	-7	-7	-7	-7	-7	-7	-7
Cycling interval capacity for heating		P <sub>cyc,h</sub>	kW	Not applicable															
Degradation co-efficient (**)		C <sub>dh</sub>	—	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>																			
T <sub>j</sub> = -7°C		COP <sub>d</sub>	—	1.99	2.84	1.99	2.84	1.97	2.74	1.97	2.74	1.91	2.70	1.91	2.70	2.05	2.98	2.05	2.98
T <sub>j</sub> = +2°C		COP <sub>d</sub>	—	3.11	4.40	3.11	4.40	3.11	4.38	3.11	4.38	3.18	4.35	3.18	4.35	3.24	4.46	3.24	4.46
T <sub>j</sub> = +7°C		COP <sub>d</sub>	—	4.25	5.85	4.25	5.85	4.29	6.04	4.29	6.04	4.52	6.32	4.52	6.32	4.47	5.89	4.47	5.89
T <sub>j</sub> = +12°C		COP <sub>d</sub>	—	5.91	7.39	5.91	7.39	6.06	7.43	6.06	7.43	6.37	8.07	6.37	8.07	5.97	7.14	5.97	7.14
T <sub>j</sub> = bivalent temperature		COP <sub>d</sub>	—	1.99	2.84	1.99	2.84	1.97	2.74	1.97	2.74	1.91	2.70	1.91	2.70	2.05	2.98	2.05	2.98
T <sub>j</sub> = operation limit temperature		COP <sub>d</sub>	—	1.71	2.68	1.71	2.68	1.73	2.67	1.73	2.67	1.69	2.35	1.69	2.35	1.72	2.71	1.72	2.71
T <sub>j</sub> = -15°C (if TOL < -20°C)		COP <sub>d</sub>	—	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Operation limit temperature		TOL	°C	-10	-10	-10	-10	-10	-10	-10	-10	-10	-10	-10	-10	-10	-10	-10	-10
Cycling interval efficiency		COP <sub>cyc</sub>	—	Not applicable															
Heating water operating limit temperature		WTOL	°C	55	55	55	55	55	55	55	55	55	55	55	55	55	55	55	55
Power consumption in modes other than active mode																			
Off mode		P <sub>OFF</sub>	kW	0.004	0.004	0.004	0.004	0.004	0.004	0.004	0.004	0.004	0.004	0.004	0.004	0.004	0.004	0.004	0.004
Thermostat-off mode		P <sub>TO</sub>	kW	0.013	0.012	0.013	0.012	0.013	0.012	0.013	0.012	0.013	0.014	0.014	0.014	0.021	0.020	0.021	0.020
Standby mode		P <sub>SB</sub>	kW	0.010	0.010	0.010	0.010	0.010	0.010	0.010	0.010	0.010	0.010	0.010	0.010	0.008	0.008	0.008	0.008
Crankcase heater mode		P <sub>CK</sub>	kW	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
Supplementary heater																			
Rated heat output (*)		P <sub>sup</sub>	kW	0.9	1.0	0.9	1.0	1.3	1.1	1.3	1.1	1.2	0.9	1.2	0.9	1.1	1.2	1.1	1.2
Type of energy input		Electric																	
Other items																			
Capacity control		Variable																	
Sound power level		Hydraulic unit	L <sub>WA</sub>	dB	40	-	40	-	40	-	40	-	40	-	40	-	40	-	40
		Outdoor unit	L <sub>WA</sub>	dB	57	-	57	-	57	-	57	-	60	-	60	-	62	-	62
Annual energy consumption		Q <sub>HE</sub>	kWh	3035	2322	3035	2322	3411	2594	3411	2594	3903	2982	3903	2982	5083	3875	5083	3875
Emissions of nitrogen oxides		NO <sub>x</sub>	mg/kWh	Not applicable															
Rated air flow rate		Outdoor unit	—	m <sup>3</sup> /h	2100	1640	2100	1640	2100	2100	2100	2100	3120	3120	3120	4130	4130	4130	4130
Declared load profile		L L L L L L L L L L L L L L L L L L L L																	
Daily electricity consumption		Q <sub>elec</sub>	kWh	-	-	3.750	3.750	-	-	3.750	3.750	-	-	3.750	3.750	-	-	3.750	3.750
Annual electricity consumption		AEC	kWh	-	-	793	793	-	-	793	793	-	-	793	793	-	-	793	793
Water heating energy efficiency		η <sub>wh</sub>	%	-	-	130	130	-	-	130	130	-	-	130	130	-	-	130	130
Daily fuel consumption		Q <sub>fuel</sub>	kWh	Not applicable															
Contact details																			
FUJITSU GENERAL (EURO) GmbH Fritz-Vomfelde-Strasse 26-32 40547 Düsseldorf, Germany																			

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output P<sub>rated</sub> is equal to the design load for heating P<sub>design,h</sub>, and the rated heat output of a supplementary heater P<sub>sup</sub> is equal to the supplementary capacity for heating sup (T<sub>j</sub>).

(\*\*) If C<sub>dh</sub> is not determined by measurement then the default degradation coefficient is C<sub>dh</sub> = 0.9.

(\*\*\*) Possible with using an optional component.