

# Technical Datasheet



**Trade name :** Remove AD(hesive) 200  
**Reviewed:** 19.12.2018  
**Date of print :** 18.01.2019

**Page :** 1 of 1

## Description

Remove AD(hesive) 200 is a slightly alkaline aqueous cleaner with high solvency for the removal of cured adhesives and sealants. The water-based cleaner, with pleasant smell, is based on renewable raw materials from recycling products. These natural, active ingredients give the cleaner a strong dissolving property. The surface is not attacked and the original look is restored. A special aluminium protective formula prevents tarnishing of aluminium, brass and non-ferrous metals.

## Chemical characterisation

Water-based light alkaline cleaning agent.

## Classification according to Regulation (EC) No.1272/2008 [CLP]

Aquatic Chronic 3 ; H412 - Hazardous to the aquatic environment : Chronic 3 ; Harmful to aquatic life with long lasting effects.  
Skin Sens. 1 ; H317 - Skin sensitisation : Category 1 ; May cause an allergic skin reaction.

## Transport information

ADR : -

## Water hazard class (Classification according to VwVwS)

Water hazard class : 2 (hazardous to water)

## Labelling for contents according to regulation (EC) No. 648/2004

< 5 % anionic surfactants  
5 - 15 % non-ionic surfactants

## Safety equipment

Eye / Face protection:	suitable safety goggles acc. EN 166	In case of splash
Hand protection:	suitable gloves type EN 374	In case of possible or enduring skin contact
Respiratory protection:	Combination filtering device DIN EN 14387	In case of exceeding exposure limit values

## Application

Remove AD(hesive) 200 is ready to use and suitable for both manual and machine use – for ultrasonic and dipping bath applications. For cleaning heavily soiled components of various materials, even at room temperature. If required, heating up to 45 °C is possible, thereby increasing the cleaning performance.

*Note: Not suitable for use in high-pressure cleaning machines.*

## Technical data

Appearance :	liquid		
Colour :	yellow/redish		
Odour :	characteristic		
Boiling temperature :	ca. 100 °C	Solidifying temperature :	< 0 °C
Flash point :	not relevant	Ignition temperature :	not relevant
Lower explosion limit :	not relevant	Upper explosion limit :	not relevant
Density (20 °C) :	ca. 1,004 g/cm <sup>3</sup>	pH-value :	8,4
VOC (EG) :	2,2 Wt %	VOC (CH) :	3,4 Wt %

## Storage

Keep container tightly closed. Keep/store only in original container. Protect against sub-zero temperatures. Optimized storage temperature is between 2 °C up to 35 °C. The product is storable in closed original packaging for at least 12 months. Starting date is the date of production.

Storage class (acc. TRGS 510): 12

## Disposal advices

The waste codes are recommendations based on the schedule use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances.

**Waste code acc. EWC/AVV for unused product**  
20 01 29\* detergents containing dangerous substances.

**Waste code acc. EWC/AVV for packaging**  
15 01 02 plastic packaging

The waste code for used product depends on the kind of contaminations that were washed from spare parts and may be different to those stated here.

Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.

## Order information

<b>A500740</b>	500 ml PET bottle with trigger – TU: 20 x 500 ml
<b>A020740</b>	20 l jerry can
<b>A200740</b>	200 l Drum
<b>A100740</b>	1000 l IBC