

*Individuell beraten.
Zuverlässig verpackt.*

Technisches Datenblatt

Kirsch Artikel-Nr. 14W200

APPLICATION: PACKAGING TAPE - ACRYLIC

Item	BACKING		Adhesive	Total Thickness (µm)	Adhesivity on steel (N/cm) (AFERA 5001)	Tensile strength (N/cm) (AFERA 5004)	Elongation at break (%) (AFERA 5004)
	Type	Thickness (µm)					
Tolerance				+/- 5%	+/- 10%	+/- 10%	+/- 15%
A32	BOPP	32	Acrylic (Water based)	52	2,2	45	160

Stocking time

We recommend to use the product within 6 months from the delivery.

Stocking conditions

The product has to be stocked in a dry environment, at a temperature between 15°C and 25°C. The product must be stored protected from dust, humidity and direct sun exposure. It must be stored horizontally and kept in the original packing.

Use

If the storage temperature has been different from what suggested, bring the tape back to that temperature before application.

Before applying the tape, remove any trace of dust or any other dirt on the carton and press the tape down thoroughly for a perfect and time lasting adherence.

Important:

The mentioned data stem from an average analysis carried out on our standard production and may undeunexpected changes. Therefore they are not binding for our company.

Sämtliche Angaben und Informationen beruhen auf den Angaben unserer Hersteller. Für deren Korrektheit können wir daher keine Haftung übernehmen.

