



**MATERIALI  
MATERIALS**

|                                       |   |
|---------------------------------------|---|
| <b>Otturatore:</b><br><b>Shutter:</b> | <b>Ottone</b><br><b>Brass</b>                 |
| <b>Corpo Valvola:</b><br><b>Body:</b> | <b>Ottone</b><br><b>Brass</b>                 |
| <b>Tappo:</b><br><b>Tap:</b>          | <b>Ottone</b><br><b>Brass</b>                 |
| <b>Molle:</b><br><b>Springs:</b>      | <b>Acciaio Inox</b><br><b>Stainless steel</b> |
| <b>Manopola:</b><br><b>Knob:</b>      | <b>PA6</b><br><b>PA6</b>                      |

**CARATTERISTICHE FUNZIONALI  
FUNCTIONAL CHARACTERISTICS**

|   |
|---|
| -Pressione nominale: <b>PN10</b><br>Nominal pressure: <b>PN10</b>   |
| -Pressione max esercizio (dinamica): <b>5 bar</b><br>Max. working pressure (dynamic): <b>5 bar</b>  |
| -Temperatura max ingresso: <b>85°C</b><br>Max. ingoing temperature: <b>85°C</b>   |
| -Massimo rapporto tra le pressioni in ingresso: (H/C o C/H): <b>2:1</b><br>Max. ratio between the input pressures : (H/C o C/H): <b>2:1</b> |
| - <b>Kvs 4 (m3/h)</b>   |

MODIFICHE  
ALTERATIONS

|   |                  |                     |  |            |             |               |                |                 |  |                              |       |              |          |
|---|------------------|---------------------|--|------------|-------------|---------------|----------------|-----------------|--|------------------------------|-------|--------------|----------|
| TOLLERANZE GENERALI<br>GENERAL TOLERANCES | SCALA<br>SCALE   | 1:2                 | VALORI ANGOLARI<br>ANGULAR VALUES ±30' |            |             |               |                |                 | MATERIALE / MATERIAL                                     | DISEGN.<br>DRAW              | ZANNI | DATA<br>DATE | 23/11/15 |
|   |                  |                     | fino<br>a 3                            | > 3<br>a 6 | > 6<br>a 30 | > 30<br>a 120 | > 120<br>a 400 | > 400<br>a 1000 |  | CONTR.<br>CHECK              |       | DATA<br>DATE |          |
|   |                  | PLASTICA<br>PLASTIC | ±0.15                                  | ±0.17      | ±0.25       | ±0.4          | ±1             | ±2.5            |  |                              |       |              |          |
|   |                  | METALLO<br>METAL    | ±0.05                                  | ±0.05      | ±0.1        | ±0.15         | ±0.2           | ±0.3            | TRATT. TERMICO E/O SUPERF.<br>HEAT/SUPERFICIAL TREATMENT | CORRISPONDE A/CORRESPONDS TO |       |              |          |
|   |                  | METALLO<br>METAL    | ±0.1                                   | ±0.1       | ±0.2        | ±0.3          | ±0.5           | ±0.8            |  | SOSTITUISCE IL/SUBSTITUTES   |       |              |          |
|   | METALLO<br>METAL | ±0.2                | ±0.3                                   | ±0.5       | ±0.8        | ±1.2          | ±2             |                 | SOSTITUITO DA/SUBSTITUTED BY                             |                              |       |              |          |



**VALVOLA RAW KVS4 25E**  
**30-80°C INT.93 1PZ**

Referred to law terms, MUT SpA reserves the ownership on this drawing and prohibits to reproduce or communicate it without authorization

DISEGNO / DRAWING

**7.030.02174-00**

DIMENSIONI IN mm  
DIMENSIONS IN mm

