

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.02.2021

Version: 1.00

Revision: 01.10.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Trade name:** SONAX PROFILINE Waterspot Remover**Article number:**

02753000

UFI: 3UN3-A00R-R00F-Y28T**1.2 Relevant identified uses of the substance or mixture and uses advised against****Sector of Use**

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC35 Washing and cleaning products (including solvent based products)**Application of the substance / the mixture** Car care product**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

United Kingdom:

Saxon

Everland Road,

Hungerford, Berkshire, RG17 0DX, UK

Tel: 01488 689 400 | Fax: 01488 684317

e-mail: info@saxon-brands.com**1.4 Emergency telephone number:****European Union:** +49 (0) 89 19240 (Poison Centre Munich)**United Kingdom:** 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS05

Signal word Danger**Hazard-determining components of labelling:**

Siloxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di-Me

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.02.2021

Version: 1.00

Revision: 01.10.2019

(Contd. of page 1)

P280 Wear protective gloves/eye protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER/doctor.
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards**Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures**Description:** Tensides, care additives, alcohol in aqueous solution.**Dangerous components:**

CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35-xxxx	1-Methoxy-2-propanol ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	10-<15%
CAS: 5131-66-8 EINECS: 225-878-4 Reg.nr.: 01-2119475527-28-xxxx	3-butoxypropan-2-ol ⚠ Skin Irrit. 2, H315; ⚠ Eye Irrit. 2, H319	5-<10%
CAS: 71750-79-3 EC number: 615-336-9	Siloxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di-Me ⚠ Skin Corr. 1B, H314	3-<5%
CAS: 69011-36-5 EC No 931-138-8	isotridecanol,ethoxylated (>5-20EO) ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302 Specific concentration limits: Eye Dam. 1; H318: C ≥ 10 % Eye Irrit. 2; H319: 1 % ≤ C < 10 %	1-<3%
Regulation (EC) No 648/2004 on detergents / Labelling for contents		
non-ionic surfactants		<5%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures**General information:** Remove soiled clothing**After inhalation:** Supply fresh air; consult doctor in case of complaints.**After skin contact:**

Wash the areas of skin affected with water and a mild detergent.

If symptoms persist consult doctor.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.**After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Eye irritation / Eye damage

Skin irritation

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media**Suitable extinguishing agents:**

Foam

Fire-extinguishing powder

(Contd. on page 3)

(Contd. of page 2)

Carbon dioxide

Water spray

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Carbon dioxide (CO₂)

Carbon monoxide (CO)

Silicon oxides

Nitrogen oxides (NO_x)

5.3 Advice for firefighters

Protective equipment:

The normal measures for firefighting are to be taken.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Use only in well ventilated areas.

Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Store receptacle in a well ventilated area.

Keep container tightly sealed.

Protect from heat and direct sunlight.

Protect from frost.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 107-98-2 1-Methoxy-2-propanol

WEL (Great Britain)	Short-term value: 560 mg/m ³ , 150 ppm
	Long-term value: 375 mg/m ³ , 100 ppm
	Sk

IOELV (EU)	Short-term value: 568 mg/m ³ , 150 ppm
	Long-term value: 375 mg/m ³ , 100 ppm
	Skin

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.02.2021

Version: 1.00

Revision: 01.10.2019

(Contd. of page 3)

Regulatory information

WEL (Great Britain): EH40/2018

IOELV (EU): (EU) 2017/164

DNELs**CAS: 107-98-2 1-Methoxy-2-propanol**

Oral	DNEL	3.3 mg/kg (consumer) (long-term / systemic effects)
Dermal	DNEL	18.1 mg/kg (consumer) (long-term / systemic effects)
		50.6 mg/kg (worker) (long-term / systemic effects)
Inhalative	DNEL	43.9 mg/m ³ (consumer) (long-term / systemic effects)
		553.5 mg/m ³ (worker) (short-term / local effects)
		369 mg/m ³ (worker) (long-term / systemic effects)

CAS: 5131-66-8 3-butoxypropan-2-ol

Oral	DNEL	12.5 mg/kg (consumer) (longterm systematic effects)
Dermal	DNEL	22 mg/kg (consumer) (longterm systematic effects)
		52 mg/kg (worker) (longterm systematic effects)
Inhalative	DNEL	43 mg/m ³ (consumer) (longterm systematic effects)
		147 mg/m ³ (worker) (longterm systematic effects)

PNECs**CAS: 107-98-2 1-Methoxy-2-propanol**

PNEC	100 mg/l (STP)
	100 mg/l (water (intermittent release))
	10 mg/l (water (fresh water))
	1 mg/l (water (sea water))
PNEC	2.47 mg/kg (gro)
	41.6 mg/kg (sediment (fresh water))
	4.17 mg/kg (sediment (sea water))

CAS: 5131-66-8 3-butoxypropan-2-ol

PNEC	10 mg/l (sewage plant)
	5.25 mg/l (sporadic release)
	0.525 mg/l (water (fresh water))
	0.0525 mg/l (water (sea water))
PNEC	2.36 mg/kg (sediment (fresh water))
	0.236 mg/kg (sediment (sea water))
	0.16 mg/kg (soil)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls**Suitable technical control devices**

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Personal protective equipment:**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Respiratory protection:

Not required in normal cases

Ensure good ventilation/exhaustion at the workplace.

Protection of hands: Protective gloves

Material of gloves

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 mm

[EN 374]

Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min)

(Contd. on page 5)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.02.2021

Version: 1.00

Revision: 01.10.2019

(Contd. of page 4)

Eye protection:

Safety glasses
[EN 166]

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:	Fluid
Colour:	Colourless
Odour:	Gently, of ammonia
Odour threshold:	Not determined.

pH-value at 20 °C: 3.0 - 3.5

Change in condition

Melting point/freezing point: Undetermined.
Initial boiling point and boiling range: 120 - 175 °C

Flash point: 66.5 °C (DIN 51755)

Flammability (solid, gas): Not applicable.

Decomposition temperature: Not determined.

Auto-ignition temperature: Not determined.

Explosive properties: Not determined.

Explosion limits:

Lower: Not determined.
Upper: Not determined.

Vapour pressure: Not determined.

Density at 20 °C: 0.99 - 1.00 g/cm³

Relative density Not determined.

Vapour density Not determined.

Evaporation rate Not determined.

Solubility in / Miscibility with water:

Partly miscible.

Partition coefficient: n-octanol/water: Not determined.

Viscosity:

Flow time at 20 °C 10 - 12 s (DIN EN ISO 2431/4mm)

9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No dangerous reactions known.

10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid

Keep ignition sources away - Do not smoke.

Protect from heat.

See Section 7 for information on safe handling.

10.5 Incompatible materials: strong oxidizing agents

10.6 Hazardous decomposition products:

Carbon monoxide

Carbon dioxide (CO₂)

Silicon oxides

Nitrogen oxides (NO_x)

GB

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.02.2021

Version: 1.00

Revision: 01.10.2019

(Contd. of page 5)

SECTION 11: Toxicological information

11.1 Information on toxicological effects There are no toxicological findings on this mixture.

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

CAS: 107-98-2 1-Methoxy-2-propanol

Oral	LD50	4,016 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC0 / 6h	>7,000 ppm (rat)

CAS: 5131-66-8 3-butoxypropan-2-ol

Oral	LD50	3,300 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)
Inhalative	LC50 / 4h	>3.5 mg/l (rat) (OECD 403)

CAS: 71750-79-3 Siloxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di-Me

Oral	LD50	>2,000 mg/kg (rat)
------	------	--------------------

CAS: 69011-36-5 isotridecanol,ethoxylated (>5-20EO)

Oral	ATE	500 mg/kg (Ratte)
------	-----	-------------------

Primary irritant effect:

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

None of the ingredients are known to have effects which are carcinogenic, mutagenic or harmful to reproduction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity There are no ecotoxicological data available on this mixture.

Aquatic toxicity:

CAS: 107-98-2 1-Methoxy-2-propanol

LC50 / 96h	>6,800 mg/l (Leuciscus idus) (DIN38412)
LC50 / 48h	23,300 mg/l (Daphnia magna)
EC50	>1,000 mg/l (Pseudokirchneriella subcapitata) (7d)
EC50/3h	>1,000 mg/l (activated sludge) (OECD 209)

CAS: 5131-66-8 3-butoxypropan-2-ol

LC50 / 96h	>560-1,000 mg/l (Poecilla reticulata) (OECD 203)
EC50/3h	>1,000 mg/l (activated sludge) (OECD 209)
EC50 / 48h	>1,000 mg/l (Daphnia magna) (OECD 202)
EC50 / 96 h	>1,000 mg/l (Pseudokirchneriella subcapitata)

12.2 Persistence and degradability

CAS: 107-98-2 1-Methoxy-2-propanol

Biodegradation	90-100 % (OECD 301E)
----------------	----------------------

CAS: 5131-66-8 3-butoxypropan-2-ol

Biodegradation	90 % (OECD301E/92/69/EWG, C4.-B)
----------------	----------------------------------

(Contd. on page 7)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.02.2021

Version: 1.00

Revision: 01.10.2019

(Contd. of page 6)

12.3 Bioaccumulative potential**CAS: 107-98-2 1-Methoxy-2-propanol**

log Kow | ≤0.43 log Kow (25°C)

12.4 Mobility in soil No further relevant information available.**Additional ecological information:****General notes:** The product may not be released into the environment without control.**12.5 Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Waste classified as hazardous according to Annex III to Directive 2008/98/EC.

Recommendation Waste must be disposed of while observing the local, official regulations.**European waste catalogue**

1) Disposal / product

2) Disposal / contaminated packaging

07 06 04* | other organic solvents, washing liquids and mother liquors

15 01 10* | packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information**14.1 UN-Number**
ADR, IMDG, IATA

Void

14.2 UN proper shipping name
ADR, IMDG, IATA

Void

14.3 Transport hazard class(es)
ADR, ADN, IMDG, IATA
Class

Void

14.4 Packing group
ADR, IMDG, IATA

Void

14.5 Environmental hazards:
Marine pollutant:

No

14.6 Special precautions for user

Not applicable.

14.7 Transport in bulk according to Annex II of
Marpol and the IBC Code

Not applicable.

UN "Model Regulation":

Void

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****European Directives:**

EC/1907/2006 (REACH)

EC/1272/2008 (CLP)

EC/648/2004

National regulations:**Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

GB

(Contd. on page 8)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.
 H302 Harmful if swallowed.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation Serious eye damage/eye irritation	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
--	--

Abbreviations and acronyms:

NOEL = No Observed Effect Level
 NOEC = No Observed Effect Concentration
 LC = Lethal Concentration
 EC50 = half maximal effective concentration
 log POW = Octanol / water partition coefficient
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 ATE: acute toxicity estimate
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 DNEL: Derived No-Effect Level (REACH)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 IOELV = indicative occupational exposure limit values
 Flam. Liq. 3: Flammable liquids – Category 3
 Acute Tox. 4: Acute toxicity - oral – Category 4
 Skin Corr. 1B: Skin corrosion/irritation – Category 1B
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3